

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SW 1/4 NE 1/4	SECTION NUMBER 34	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

2	WATER WELL OWNER:	DYER, Kathy	
	RR#,ST. ADDRESS,BOX #:	6018 W. 34th St. N.	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
NW	NE
X	
SW	SE
S	

1 Mile W E

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:

Depth of groundwater Encountered: ft.

WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/9/05

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter 12 in. to 40 ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

5	TYPE OF CASING USED:					CASING JOINTS:	☒ Glued ☐ Threaded ☐ Welded ☐ Clamped
	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)		
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26		

Blank casing diameter	5	in.	to	30	ft.,	Dia.	in.	to	ft.,	Dia.	in.	to	ft.
Casing height above land surface:	12	in.,	Weight:	2.35	lbs. / ft.	Wall thickness or gauge No.	.214						
TYPE OF SCREEN OR PERFORATION MATERIAL:													
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)								
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)								

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)	

SCREEN - PERFORATION INTERVAL	From	30	ft.	to	40	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to	40	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.

GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug	
Grout Intervals:	From	4 ft.	to 24 ft.,	From	ft.	to	ft.,
What is the nearest source of possible contamination:							
1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well		
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)		
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage				
Direction from well? North				How many feet? 50 feet plus			

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/9/2005 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No.	236	This water well record was completed on (mo/day/year)	5-13-2005
--	------------	---	------------------

under the business name of **Harp Well & Pump Service Inc.** by (signature) *Jo dd S. Harp*