

1 LOCATION OF WATER WELL: Fraction 1/4 3/4 1/2 1/4 3/8 Section Number 33 Township Number T 26 S Range Number R 1 EW

County: Sebecus Distance and direction from nearest town or city street address of well if located within city? Corner of Pepperidge & Pepperidge Ct. 100' EAST

2 WATER WELL OWNER: Tom Sanders RR#, St. Address, Box #: 11820 W. Albert Circle Mayze, MS 39067 City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITHIN SECTION BOX: AN "X" IN SECTION BOX: [Diagram showing a 36x36 section box with an 'X' in the SE corner]

4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION: 15 ft. Depth(s) Groundwater Encountered: 15 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL: 15 ft. below land surface measured on mo/day/yr Pump test data: Well water was 15 ft. after 15 hours pumping 15 gpm Est. Yield: 15 gpm Well water was 15 ft. after 15 hours pumping 15 gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 5 in. to 70 ft. Dia 2 in. to 100 ft. Dia Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160 PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 70 ft. to 84 ft. From 15 ft. to 84 ft. GRAVEL PACK INTERVALS: From 15 ft. to 84 ft. From 15 ft. to 84 ft.

6 GROUT MATERIAL: 1 Neat cement 15 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 15 ft. From 15 ft. to 100 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? east How many feet? 100

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-20-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 740 This Water Well Record was completed on (mo/day/yr) 10-20-04 under the business name of Weninger Drilling Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.