

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SW 1/4 SW 1/4	SECTION NUMBER 28	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3945 Lake Ridge Ct. Wichita, Kansas

2	WATER WELL OWNER:	CONRADY, David			Board of Agriculture, Division of Water Resource
	RR#,ST. ADDRESS,BOX #:	3945 Lake Ridge Ct.			
	CITY, STATE:	Wichita, Kansas	ZIP CODE:	Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

W E

N S

NW NE SW SE

X

4 DEPTH OF COMPLETED WELL: **50** ft. ELEVATION: _____ ft.

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL **15** FT. BELOW LAND SURFACE MEASURED ON **10/3/05**

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter **12** in. to **50** ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? YES NO

5 TYPE OF CASING USED:		1. Steel		3. RPM (SR)		5. Wrought iron		7. Fiberglass		9. Other (Specify below)		CASING JOINTS: <u>Glued</u>		Threaded							
		<u>2. PVC</u>		4. ABS		6. Asbestos-Cement		8. Concrete tile		SDR-26		Welded		Clamped							
Blank casing diameter		5 in.		to		38 ft.,		Dia.		in.		to		ft.							
Casing height above land surface:		12 in.,		Weight:		2.35		lbs. / ft.		Wall thickness or gauge No.		.214									
TYPE OF SCREEN OR PERFORATION MATERIAL:																					
1. Steel		3. Stainless Steel		5. Fiberglass		<u>7. PVC</u>		9. ABS		11. Other (specify)											
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:																					
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)											
2. Louvered shutter		4. Key punched		6. Wire wrapped		<u>8. Saw cut</u>		10. Other (specify)													
SCREEN - PERFORATION INTERVAL		From		38		ft.		to		50		ft.,		From		ft.		to		ft.	
		From				ft.		to				ft.,		From		ft.		to		ft.	
GRAVEL PACK INTERVALS:		From		24		ft.		to		50		ft.,		From		ft.		to		ft.	
		From				ft.		to				ft.,		From		ft.		to		ft.	

6	GROUT MATERIALS:											
	1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug			
	Grout Intervals:	From 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.	
	What is the nearest source of possible contamination:											
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well	
	2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)	
	3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage					
	Direction from well? North					How many feet? 10 feet plus						

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **10/03/2005** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **10/07/2005**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *J. d. S. Harp*