

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 28	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

7904 Havenhurst		Wichita, Kansas	
2	WATER WELL OWNER:	TOPPING, Jeff	
	RR#,ST. ADDRESS,BOX #:	7904 Havenhurst	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 47 ft. ELEVATION: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/8/06 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 47 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
--	---

5 TYPE OF CASING USED:		9. Other (Specify below)		CASING JOINTS:	
1. Steel	3. RPM (SR)	7. Fiberglass	SDR-26		Glued
2. PVC	4. ABS	8. Concrete tile			Welded
Blank casing diameter		5 in.	to	27 ft.,	Dia.
		in.	to	ft.,	in.
Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.
					.214
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL		From	27 ft.	to	47 ft.,
		From	ft.	to	ft.,
GRAVEL PACK INTERVALS:		From	24 ft.	to	47 ft.,
		From	ft.	to	ft.,

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:	From 4 ft.	to 24 ft.	From	ft.	to	ft.	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage							
	Direction from well? East				How many feet? 12						

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **7/08/2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **7/10/2006**

under the business name of **Harp Well and Pump Service** by (signature) *J. d. S. Harp*