

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 28	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

3834 N. Lake Crest		Wichita, Kansas	
2	WATER WELL OWNER:	SCHELLFLER, John	
	RR#,ST. ADDRESS,BOX #:	3834 N. Lake Crest	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

4 DEPTH OF COMPLETED WELL:		50	ft.	ELEVATION:		
Depth of groundwater Encountered:			ft.			ft.
WELL'S STATIC WATER LEVEL		10	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	8/2/06	
Pump test data:		Well water was		ft. after	hours of pumping @	gpm
Est. Yield:	gpm	Well water was		ft. after	hours of pumping @	gpm
Bore Hole Diameter	12	in.	to	50	ft.	and
					in.	to
						ft.
WELL WATER TO BE USED AS:						
1. Domestic	3. Feedlot	5. Public water supply	7. Lawn and garden only		9. Dewatering	11. Injection well
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning		10. Monitoring well	
Was a chemical/bacteriological sample submitted to Department?			YES		NO	
			Was Water Well Disinfected?		YES	
					NO	

TYPE OF CASING USED:				9. Other (Specify below)		CASING JOINTS:	
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	SDR-26		☒ Glued	☐ Threaded
☒ 2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile			☐ Welded	☐ Clamped
Blank casing diameter		5 in.	to	23 ft.,	Dia.	in.	to
Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel	3. Stainless Steel	5. Fiberglass	☒ 7. PVC	9. ABS	11. Other (specify)		
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
2. Louvered shutter	4. Key punched	6. Wire wrapped	☒ 8. Saw cut	10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From	30 ft.	to	50 ft.,	From	ft.
		From	ft.	to	ft.,	From	ft.
GRAVEL PACK INTERVALS:		From	24 ft.	to	50 ft.,	From	ft.
		From	ft.	to	ft.,	From	ft.

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:	From 4 ft.	to 24 ft.	From	ft.	to	ft.	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage							
	Direction from well? East				How many feet? 15						

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **8-2-2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **8-4-2006**

under the business name of **Harp Well and Pump Service** by (signature) *J o d d S. H a r p*