

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 SW 1/4	SECTION NUMBER 2	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
---	--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
25th N. and West St. Wichita, Kansas (6 logs on 1 permit)

2	WATER WELL OWNER:	WICHITA, CITY OF		Board of Agriculture, Division of Water Resource
	RR#,ST. ADDRESS,BOX #:	455 N. Main		
	CITY, STATE:	Wichita, Kansas	ZIP CODE:	Application Number: 20060190

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: _____ ft. Depth of groundwater Encountered: _____ ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/31/06 Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 48 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. <u>Dewatering</u> 11. Injection well 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
--	--

5 TYPE OF CASING USED: 1. Steel <u>2. PVC</u> 3. RPM (SR) 4. ABS		5. Wrought Iron 6. Asbestos-Cement 7. Fiberglass 8. Concrete tile		9. Other (Specify below) SDR-26		CASING JOINTS: Glued Welded		Threaded Clamped			
Blank casing diameter		8	in.	to	20	ft.,	Dia.	in.	to	ft.	
Casing height above land surface:		12	in.,	Weight:	5.52	lbs. / ft.	Wall thickness or gauge No.	.332			
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel		3. Stainless Steel		5. Fiberglass		<u>7. PVC</u>		9. ABS		11. Other (specify)	
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)	
2. Louvered shutter		4. Key punched		6. Wire wrapped		<u>8. Saw cut</u>		10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From	20	ft.	to	38	ft.,	From	ft.	to	ft.
		From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:		From	20	ft.	to	48	ft.,	From	ft.	to	ft.
		From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:												
	1. Neat cement		2. Cement Grout		3. Bentonite		Other			bentonite hole plug			
	Grout Intervals:	From	0	ft.	to	20	ft.,	From		ft.	to		ft.
	What is the nearest source of possible contamination:												
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well							
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)							
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage	None Apparent								
	Direction from well?				How many feet?								

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **7-31-2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **8-2-2006**

under the business name of **Harp Well and Pump Service** by (signature) *J o d d S. H a r p*