

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: SW 1/4 SW 1/4 SE 1/4

Distance and direction from nearest town or city street address of well if located within city? 10909 W. Waterside Ct.

2 WATER WELL OWNER:

RR#, St. Address, Box # JFF Schoen

City, State, ZIP Code

Section Number 30

Township Number T 26S

Range Number R 1E

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude:

Longitude:

Elevation:

Datum:

Data Collection Method:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

-- NW --

-- NE --

-- SW --

-- SE --

X

E

S

4 DEPTH OF COMPLETED WELL

60 ft.

Depth(s) Groundwater Encountered (1) 18 ft. (2) 50 ft. (3) 60 ft.

WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr.

Pump test data: Well water was 50 gpm: Well water was 50 ft. after 50 hours pumping 50 gpm

Est. Yield. 50 gpm: Well water was 50 ft. after 50 hours pumping 50 gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 7 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr

Sample was submitted. Water well disinfected? Yes X No X

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile

2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)

CASING JOINTS: Glued X Clamped X

Welded X

Threaded X

Blank casing diameter 5 in. to 5 ft., Diameter. 2.40 in. to 2.40 ft., Diameter 1.60 in. to 1.60 ft.

Casing height above land surface 12 in., Weight 2.40 lbs./ft. Wall thickness or gauge No. 1.60

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)

2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 60 ft., From 30 ft. to 60 ft., From 30 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From 20 ft. to 60 ft., From 20 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 30 ft., From 30 ft. to 60 ft., From 60 ft. to 60 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? 5 How many feet? 13

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	topsoil			
1	11	clay			
11	28	fine sand			
28	35	med sand			
35	38	clay			
38	43	fine sand			
43	50	med sand			
50	60	gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/21/06 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 340 This Water Well Record was completed on (mo/day/year) 10/29/06

under the business name of Wendy Schilling Inc by (signature) Wendy Schilling

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.