


1	LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 NE 1/4 SW 1/4	SECTION NUMBER 28	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

8110 Palmetto Wichita, Kansas

2	WATER WELL OWNER:	FRESH, Robert	
	RR#,ST. ADDRESS,BOX #:	8110 Palmetto	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	ZIP CODE: Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4. DEPTH OF COMPLETED WELL: **50** ft. ELEVATION: _____

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL **10** FT. BELOW LAND SURFACE MEASURED ON **12/16/06**

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter **12** in. to **50** ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS Blank casing diameter 5 in. to 35 ft., Dia. in. to ft., Dia. in. to ft.		5. Wrought Iron 7. Fiberglass 9. Other (Specify below) 6. Asbestos-Cement 8. Concrete tile SDR-26		CASING JOINTS: Glued Threaded Welded Clamped	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 35 ft. to 50 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 50 ft., From ft. to ft. From ft. to ft., From ft. to ft.					

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug				
	Grout Intervals:		From	4 ft.	to	24 ft.	From	ft.	to	ft.	From	ft.	to	ft.	
What is the nearest source of possible contamination:															
1. Septic tank			4. Lateral lines			7. Pit privy			10. Livestock pens			13. Insecticide storage		15. Oil well/Gas well	
2. Sewer lines			5. Cess Pool			8. Sewage lagoon			11. Fuel storage			14. Abandon water well		16. Other (specify below)	
3. Watertight sewer line			6. Seepage pit			9. Feed yard			12. Fertilizer storage						
Direction from well?										North				How many feet? 16	

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **12-16-2006** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **12-18-2006**

under the business name of **Harp Well and Pump Service** by (signature) *Todd S. Harp*