

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SE 1/4 NE 1/4	SECTION NUMBER 24	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

2	WATER WELL OWNER:	WICHITA, CITY OF	
	RR#,ST. ADDRESS,BOX #:	455 N. Main	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Wichita, Kansas	Application Number: 20060394
		ZIP CODE:	

1 Mile

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL **10** FT. BELOW LAND SURFACE MEASURED ON **1/26/07** mo/day/yr:

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter **12** in. to **60** ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic	3. Feedlot	5. Public water supply	7. Lawn and garden only	9. Dewatering	11. Injection well
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning	10. Monitoring well	12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? **YES** **NO** ; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? **YES** **NO**

5		TYPE OF CASING USED:		9. Other (Specify below)		CASING JOINTS: <u>Glued</u>		Threaded	
1. Steel		3. RPM (SR)		7. Fiberglass		Welded		Clamped	
<u>2. PVC</u>		4. ABS		8. Concrete tile		SDR-26			
Blank casing diameter		8 in.		to 20 ft.		Dia.		in. to ft.	
Casing height above land surface:		12 in.		Weight:		5.52 lbs. / ft.		Wall thickness or gauge No. .332	
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel		3. Stainless Steel		5. Fiberglass		<u>7. PVC</u>		9. ABS	
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement	
								11. Other (specify)	
								12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes	
2. Louvered shutter		4. Key punched		6. Wire wrapped		<u>8. Saw cut</u>		10. Other (specify)	
SCREEN - PERFORATION INTERVAL		From		20 ft.		to 50 ft.		From ft. to ft.	
		From		ft.		to ft.		From ft. to ft.	
GRAVEL PACK INTERVALS:		From		20 ft.		to 60 ft.		From ft. to ft.	
		From		ft.		to ft.		From ft. to ft.	

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:	From 0 ft.	to 20 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage	None Apparent						
	Direction from well?				How many feet?						

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **1-26-2007** and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) **2-1-2007**
under the business name of **Harp Well and Pump Service** by (signature) *Todd S. Harp*