

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 NE 1/4 NE 1/4	SECTION NUMBER 28	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

45th St. N. and Ridge Road, West on South side (4 permits on 1 log) Wichita, Kansas

RR#,ST. ADDRESS,BOX #: **1144 S. Seneca** Board of Agriculture, Division of Water Resource
CITY, STATE: **Wichita, Kansas** ZIP CODE: Application Number: **20090086**

4. DEPTH OF COMPLETED WELL:		40		ft.		ELEVATION:			
Depth of groundwater Encountered:				ft.				ft.	
WELL'S STATIC WATER LEVEL		8		FT. BELOW LAND SURFACE MEASURED ON		mo/day/yr:		5/12/09	
Pump test data:		Well water was		ft. after		hours of pumping @		gpm	
Est. Yield:		gpm		Well water was		ft. after		hours of pumping @	
								gpm	
Bore Hole Diameter		12		in.		to		40	
								ft. and	
								in. to	
								ft.	
WELL WATER TO BE USED AS:									
1. Domestic		3. Feedlot		5. Public water supply		7. Lawn and garden only		9. Dewatering	
								11. Injection well	
2. Irrigation		4. Industrial		6. Oil field water supply		8. Air conditioning		10. Monitoring well	
								12. Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department?				YES		NO		; If yes, what mo/day/yr was sample submitted	
				Was Water Well Disinfected?		YES		NO	

5	TYPE OF CASING USED:					CASING JOINTS:	Glued	Threaded
	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)		Welded	Clamped
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SCH-40			

Blank casing diameter **8** in. to **20** ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: **12** in., Weight: **5.52** lbs. / ft. Wall thickness or gauge No. **332**

TYPE OF SCREEN OR PERFORATION MATERIAL:

1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)

2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)

SCREEN - PERFORATION INTERVAL	From	20	ft.	to	40	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	20	ft.	to	40	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:													
	1. Neat cement			2. Cement Grout			3. Bentonite			Other	bentonite hole plug			
Grout Intervals:	From	0	ft.	to	20	ft.	From	ft.	to	ft.	From	ft.	to	ft.

What is the nearest source of possible contamination:

1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage	None Apparent	

Direction from well?

How many feet?

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/12/2009 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year) **5-14-2009**

under the business name of **Harp Well and Pump Service**

by (signature)

Todd S. Harp