

FRACTION			SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
SE 1/4	SE 1/4	SE 1/4	21	T 26 S	R 1W E/W

Distance and direction from nearest town or city: **NW corner of 45th N. and Bridge Road** **Wichita, Kansas** **(6 permits on 1 log)**

2	WATER WELL OWNER:	SENECA COUNTY			Board of Agriculture, Division of Water Resource
	RR#,ST. ADDRESS,BOX #:	1144 S. Seneca			
	CITY, STATE:	Wichita, Kansas		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
NW	NE
SW	SE
S	

1 Mile

4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:

Depth of groundwater Encountered: ft.

WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 9/10/09

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Base Hole Diameter 12 in. to 40 ft. and in. to ft.

WELL WATER TO BE USED AS:

Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Is a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

TYPE OF CASING USED:				CASING JOINTS:			
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	Glued	Threaded	
2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	Clamped	
Blank casing diameter	8	to	20	ft., Dia.	in.	to	ft.
Casing height above land surface:	12	in.,	Weight:	5.52	lbs. / ft.	Wall thickness or gauge No.	.332
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)		
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)			
SCREEN - PERFORATION INTERVAL	From	20	ft.	to	40	ft.	ft.
	From		ft.	to		ft.	ft.
GRAVEL PACK INTERVALS	From	20	ft.	to	40	ft.	ft.
	From		ft.	to		ft.	ft.

6	GROUT MATERIALS:		1. Nearest cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug	
	Grout Intervals:	From	()	ft.	to	20	ft.	From	ft.	to	ft.	ft.
What is the nearest source of possible contamination:												
1. Septic tank		4. Latrine lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well		
2. Sewer lines		5. Cess pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)		
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage		None Apparent				
Direction from well?										How many feet?		

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **9/10/2009** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **9/18/2009**

under the business name of **Harp Well and Pump Service** by (signature) *Todd S. Harp*