

1		LOCATION OF WATER WELL:		FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER		
		Sedgwick		NE 1/4 NW 1/4 NW 1/4	33	T 26 S	R 1W E/W		
Distance and direction from nearest town or city street address of well if located within city?									
		3731 N. Pepperridge		Wichita, Kansas					
2		WATER WELL OWNER:		KLAUSMEYER, CONSTRUCTION					
		RR#,ST. ADDRESS,BOX #:		10008 W. York					
		CITY, STATE:		ZIP CODE:		Application Number:			
3		LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4				DEPTH OF COMPLETED WELL: 55 ft.	
		ELEVATION:							
		Depth of groundwater Encountered:							
		WELL'S STATIC WATER LEVEL		12 FT. BELOW LAND SURFACE MEASURED ON		mo/day/yr: 5/4/11			
		Pump test data:		Well water was				ft. after hours of pumping @ gpm	
		Est. Yield:		Well water was				ft. after hours of pumping @ gpm	
		Bore Hole Diameter		12 in.		to 55 ft. and in. to ft.			
		WELL WATER TO BE USED AS:							
		1. Domestic		3. Feedlot		5. Public water supply		7. Lawn and garden only	
		2. Irrigation		4. Industrial		6. Oil field water supply		8. Air conditioning	
		Was a chemical/bacteriological sample submitted to Department?		YES		NO		; If yes, what mo/day/yr was sample submitted	
		Was Water Well Disinfected?		YES		NO			
5		TYPE OF CASING USED:		CASING JOINTS:					
		1. Steel		3. RPM (SR)		5. Wrought Iron		7. Fiberglass	
		2. PVC		4. ABS		6. Asbestos-Cement		8. Concrete tile	
		Blank casing diameter		5 in.		to 35 ft., Dia.		in. to ft. Dia. in. to ft.	
		Casing height above land surface:		12 in.,		Weight: 2.35 lbs. / ft.		Wall thickness or gauge No. .214	
		TYPE OF SCREEN OR PERFORATION MATERIAL:							
		1. Steel		3. Stainless Steel		5. Fiberglass		7. PVC	
		2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)	
		SCREEN OR PERFORATION OPENINGS ARE:							
		1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut	
		2. Louvered shutter		4. Key punched		6. Wire wrapped		8. Saw cut	
		SCREEN - PERFORATION INTERVAL		From		35 ft.		to 55 ft., From ft. to ft.	
		GRAVEL PACK INTERVALS:		From		24 ft.		to 55 ft., From ft. to ft.	
6		GROUT MATERIALS:		Other bentonite hole plug					
		Grout Intervals:		From		4 ft.		to 24 ft., From ft. to ft., From ft. to ft.	
		What is the nearest source of possible contamination:							
		1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens	
		2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage	
		3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage	
		Direction from well? West						How many feet? 10 ft. plus	
		LITHOLOGIC LOG		LITHOLOGIC LOG					
		From To		From To					
		0 3 topsoil							
		3 14 clay							
		14 20 fine sand							
		20 55 medium sand							
7		Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/4/2011 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/6/2011 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp							