

WATER WELL RECORD

SE NW SW NE

Form WWC-5

T, 26 S.

Division of Water Resources App. No.

1 LOCATION OF WATER WELL:

County: Saline

Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here ☐.

3102 Bayview

Fraction: NE 8E 1/4 NW 1/4

Section Number: 24

Township No.: T 26 S

Range Number: R 1 ☐ E ☒ W

2 WATER WELL OWNER: Mr Youngers

RR#, Street Address, Box #: 3102 Bayview

City, State, ZIP Code: Wichita KS 67204

3 LOCATE WELL WITH AN "X" IN SECTION BOX:

N

-- NW --	-- NE --
-- SW --	-- SE --

S

-----1 mile-----

4 DEPTH OF COMPLETED WELL 32 ft.

Depth(s) Groundwater Encountered (1) 12 ft. (2) 12 ft. (3) 4-20-12 ft.

WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr. 4-20-12

Pump test data: Well water was 9 ft. after 12 hours pumping 4-20-12 gpm

EST. YIELD 9 gpm Well water was 12 ft. after 12 hours pumping 4-20-12 gpm

Bore Hole Diameter 9 in. to 12 ft., and 12 in. to 12 ft.

WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well

☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)

☐ Irrigation ☐ Industrial ☒ Domestic-lawn & garden ☐ Monitoring well

Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No

If yes, mo/day/yr sample was submitted: _____

Water well disinfected? ☐ Yes ☒ No

5 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other _____

CASING JOINTS: ☒ Glued ☐ Clamped ☐ Welded ☐ Threaded

Casing diameter 5 in. to 22 ft., Diameter 12 in. to 32 ft., Diameter 160 in. to 160 ft.

Casing height above land surface 12 in., Weight _____ lbs./ft., Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:

☐ Steel ☐ Stainless Steel ☒ PVC ☐ Other (Specify) _____

☐ Brass ☐ Galvanized Steel ☐ None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

☐ Continuous slot ☒ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)

☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify) _____

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft., From _____ ft. to _____ ft.

GRAVEL PACK INTERVALS: From 12 ft. to _____ ft., From _____ ft. to _____ ft.

6 GROUT MATERIAL: ☐ Neat cement ☒ Cement grout ☐ Bentonite ☐ Other _____

Grout Intervals: From 0 ft. to 12 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft.

What is the nearest source of possible contamination:

☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)

☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well

☒ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well

Direction from well West Distance from well 50

FROM	TO	LITHOLOGIC LOG
<u>0</u>	<u>4</u>	<u>Top Soil</u>
<u>4</u>	<u>16</u>	<u>Fine Tan Sand</u>
<u>16</u>	<u>32</u>	<u>Coarse Tan Sand</u>

FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 4-20-12 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 472 This Water Well Record was completed on (mo/day/year) 4-20-12 under the business name of Beardley Pump & Well (signature) Dave Barb

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.