		VELL REC	ORD F	orm WV		SA 82a-1			ydania a dina da da
1 LOCATION OF WATER WELL:	FRACTION SW 1/4	1 SE 1	(4 NOTHER		TION NUMBER		HIP NUMBER	1	E NUMBER
□ Sedgwick Distance and direction from nearest town or ci			/4 NE	1/4	33	T	26 S	R	1W E/W
3434 N. Beach Club		ta. Kansas	iii city:						
	UYEN, Nick	en, remons	``````	 	 				
	34 N. Beach C	lub					Board of Ag	riculture, Division	of Water Resource
CITY, STATE: \mathbf{Wi}	chita, Kansas			ZI	P CODE:		Application Nu	mber:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COM	IPLETED WEL	L: 48	B ft.		ELEVATION	l:		
WITH AN "X" IN SECTION BOX:	 Depth of groundwat	er Encountere	d:	ft.	;		ft.		ft.
	WELL'S STATIC W	ATER LEVEL	14	FT. BELO	W LAND SU	RFACE MEA	SURED ON mo	/day/yr: 1	1/30/14
NW	P	ump test data:	Well wat	er was		ft. after	hour	rs of pumping (@ gp
w X E	Est. Yield:	gpm	Well wa		46 .	ft. after		rs of pumping	,
	Bore Hole Diamet		in.	to 4	18 ft.	and	in.	tı 44	
swse	WELL WATER TO 1. Domestic	BE USED AS: 3. Feedlot		ter supply	7. Lawn ar	nd garden o	9. Dewater	iiig	Injection well r (Specify below
		4. Industrial	6. Oil field w				10. Monitor	ing well	
S	Was a chemical/bac	teriological samp			YES	NO			/yr was sample
أعار في مساور و المراجع و	submitted		 		Was W	ater Well Di	sinfected?	(YES)	NO
TYPE OF CASING USED: 1. Steel 3. RPM (5. Wroug	ht Iron	7. Fiberglass	9. O	ther (Specify	pelow) C	ASING JOINTS:		Threaded
2. PVC 4. ABS	` '	os-Cement	8. Concrete ti	le SD	R-26			Welded	Clamped
Blank casing diameter 5	in. to	38 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface:	12 _{in.,}	50,			bs. / ft.	,			214
TYPE OF SCREEN OR PERFORATION	,,		Weight:	2.33	DS. / II.	vvai	I thickness or gau	age No	214
1. Steel 3. Stainless Steel		is C	7. PVC	9. A	ABS	11.	Other (specify)		
2. Brass 4. Galvanized	6. Concrete	Tile	8. RMP (SR)	10. A	sbestos-Cem	ent 12.	None used (oper	n hole)	
SCREEN OR PERFORATION OPENI	INGS ARE:								
1. Continuous slot 3. Mill	slot 5	. Gauzed wra	pped	7. T o	rch cut	9. D	rilled holes	11. Nor	ie (open hole)
2. Louvered shutter 4. Key	punched 6	. Wire wrappe	ed	(8. S a	w cut	10. C	ther (specify)		
SCREEN - PERFORATION INTERVA	L From	38 ft	. tó	48	ft.,	From	ft.	to	rı.
SOMELY FERMION WITH THE COVE	From	SO. It			ft.,	From			
GRAVEL PACK INTERVALS:		24 ft			ft.,	From	ft. ft.	to to	
STOULD FROM THE ENVIRED.	,	ft							.,,
CROLIT MATERIALS.	From	 			ft.,	From	ft.	to	
	at cement 4 ft. to	2. Cemer			3. Bentonite			tonite hole	. 0
Grout Intervals: From What is the nearest source of possible		o 24 ft.		ft.		ft.,	From	ft.	to f
• • • • • • • • • • • • • • • • • • • •	eral lines	7. Pit privy	1	0. Livestoo	ck pens	13. Ins e	cticide storage		ell/Gas well
2. Sewer lines 5. Ces	s Pool	8. Sewage la	goon	1. Fuel sto	orage	14. Ab a	ndon water wel	16. Othe	r (specify belov
3. Watertight sewer line 6. See	page pit	9. Feed yard	•	2. Fertilize	r storage				
Direction from well? South	<u> </u>					How	many feet? 10		
From To	LITHOLOG	IC LOG	ب ر بند پندیششند	From	То		LITHOL	OGIC LO	3
0 3 topsoil			<u> </u>	<u> </u>	-				
3 8 clay 8 15 fine sand	wigo at first section is				1				
8 15 fine sand 15 32 clay and fir	ne cand			1		110 111	and the state of t		
			·				ina a ini atawa kapi a ina akisim		
32 48 medium sai						·-			
32 48 medium sai				-					
32 48 medium sa		***************************************		1					
32 48 medium sa						· · · · · · · · · · · · · · · · · · ·			
32 48 medium sa									
32 48 medium sa									
32 48 medium sa									
32 48 medium sa									
32 48 medium sa									

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/3/2014

under the business name of Harp Well and Pump Service by (signature) Todd S. Harp