				WELL R	ECOR	D Fo	rm WW		SA 82a-12				
1 LOCATION OF WATER WELL:  Sedgwick			FRACTION	1/4 SW	4.74	NW	ı	ION NUMBER	l .	IIP NUMBER	l .	ENUMBER  1W E/W	
Distance and direction	on from	nearest town or o			1/4		1/4	33	I T	26 s	R	1W E/W	
8720 W. C			Wichita,		vviii iii oity i								
2 WATER WE			AUSMEYE		TRUCT	TON							
RR#,ST. ADDR	RESS,B	OX #: 10	008 W. York							Board of Ag	riculture, Division	of Water Resour	ce
С	ITY, S	гате: ${f W}$ і	ichita, Kans	as			ZIF	CODE:		Application Nu	mber:		
3 LOCATE WELL			DEPTH OF C	OMPLETED V	WELL:	65	ft.		ELEVATION:				
── WITH AN "X" IP	N SECTI N	ON BOX:	 Depth of grounds	vater Encoun	tered:		ft.			ft.		ft.	
			WELL'S STATIC	WATER LE	√EL :	20	FT. BELO	W LAND SU	IRFACE MEAS	SURED ON mo.	/day/yr: <b>2</b>	/27/14	
NW		- NE		Pump test d	lata: V	Nell water	r was		ft. after	hour	s of pumping @	g g	ıpm
Wille w		i .	Est. Yield:	gpm	•	Well wate		_	ft. after	hou	s of pumping (	- 0.	pm
Z W		E	Bore Hole Dian		. <b>2</b> in.		to 6	<b>5</b> ft.	and	in.	to		ft.
WELL WATER TO BE USED AS:   Domestic 3. Feedlot 5. Public water sup								7. Lawn a	nd garden or	9. Dewater	mg	njection well	
1		-	2. Irrigation	4. Industri			ter supply			10. Monitor		(Specify belo	)W)
Language Commence Com			Was a chemical/l					YES	NO	; If yes,	what mo/day/		)
			submitted		<del></del>			Was V	Vater Well Dis	infected?	(YES)	NO	
5 TYPE OF 1. Stee		IG USED: 3. RPM	(SP) 5. Wro	ught Iron	7. Fib	erglass	9. Ot	her (Specify	below) CA	ASING JOINTS:	-	Threaded	
2. PVC	-	4. ABS	• /	estos-Cemen	t 8. Coi	ncrete tile	SDI	R-26			Welded	Clamped	
Blank casing dia	-	5	in. to	45 f	t., [	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
10								os. / ft.	ŕ	thickness or gau			
TYPE OF SCRE				1.,	wei	ym. 4	II.	)S. / It.	vvali	trickness or gat	ige NoZ	14	
1. Steel		Stainless Stee		lass	7. PVC	$\supset$	9. Al	BS	11. (	Other (specify)			
2. Brass	4.	Galvanized	6. Concr	ete Tile	8. RMI	P (SR)	10. A	sbestos-Cer	ment 12. I	None used (ope	n hole)		
SCREEN OR PE	ERFOR	ATION OPEN	INGS ARE:										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped							7. <b>T</b> oi	Torch cut 9. Drilled holes 11. None ( open ho					
2. Louvered s	hutter	4. Ke	y punched	unched 6. Wire wrapped			8. Saw cut		10. Other (specify)				
SCREEN - PERF	EODAT		•	45	ft.	to	65	ft.,	From		4-	r.	
JOINLEN - FEIN	ONAT	ION INTLICE	From	43	ft.	to	0.5			ft.	to	ft.	
CBAVE	I DACI	K INTERVALS		24	ft.	to	65	ft.,	From	ft.	to	ft.	
GRAVE	L FAU	NINIERVALO		27			0.5	ft.,	From -	ft.	to	ft.	
			From		ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MA		1, 140	eat cement		ment Gro		-	B. Bentonite	•	Other ben	tonite hole	plug	
Grout Interva		From	4 ft.	to <b>24</b>	ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy  10.							. Livestoc	vestock pens 13. Insecticio			cide storage 15. Oil well/Gas well		
2. Sewer lines		5. <b>Ces</b>	s Pool	8. Sewag	e lagoon	11	. Fuel sto	rage	14. Abaı	ndon water wel	l 16. Other	r (specify belo	w)
3. Watertight		-	epage pit	9. Feed y	ard	12	. Fertilize	r storage					
Direction from w		East							How	many feet? $10$	ft. plus		
From T	o		LITHOLC	GIC LOG	<u> </u>		From	То		LITHOL	OGIC LOG	}	
		opsoil											
		day						<b>-</b>					
		ine sand medium sa	nd								TOTAL CONTRACTOR OF THE OWNER OWNER OF THE OWNER O		
												······································	
<del>  </del>			<del></del>										
<del></del>			<del></del>	<del></del>						14-0-0			
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~					······································	<u> </u>					
			OME TO THE PROPERTY OF THE PRO	2000 AND DESCRIPTION OF THE PARTY OF THE PAR									анання
I/I Continue	renel a	andownor's Co	rtification: This i	untar wall wa	. 1 /	مدسده ما	) 0 ro	constructo	d or o	plugged	under my juri	ediction and	

2/27/2014 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

2/28/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp