WATER WELL RECORD Form WWC-5 KSA 82a-1212 RANGE NUMBER LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER Sedgwick NWSE SE 30 26 S 1W E/W 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 3919 N. Manchester Wichita, Kansas ROBL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 5842 N. 21st N. Wichita, Kansas ZIP CODE: 67205 CITY, STATE Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 3 ft. ft. ft. Depth of groundwater Encountered: 20 4/9/14 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: hours of pumping @ Pump test data: Well water was ft. after gpm ΝE ΝW Est. Yield: Well water was ft. after hours of pumping @ gpm gpm Φ 12 ⋽ Bore Hole Diameter to 65 ft. and in. ft. to WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES NO submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 ft. 45 Dia. ft... Dia. Blank casing diameter in. ft... in. to in. to 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 8. Saw cut 2. Louvered shutter 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 45 ft. 65 to ft., From From ft. to ft. ft. ft.. From to From ft. to ft. **GRAVEL PACK INTERVALS:** 24 ft. 65 to ft., From ft. From to ft. ft. From to ft. From ft. ft. Other **GROUT MATERIALS:** bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite 4 Grout Intervals: ft. 24 From ft., From fŧ to ft., From ft. ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line West How many feet? 10 ft. plus Direction from well? From LITHOLOGIC LOG From To LITHOLOGIC LOG Tο 0 3 tonsoil 3 15 clay 15 40 fine sand 40 medium sand 65

		İ.										
												tallows -
7	Cont	ractor's or La	ndowner's Certifi	cation: This water well	was 1. construct	ed 2, re	econstructed	l or	3.	plugged	under my jurisdic	ion and
	was cor	npleted on (m	no/day/year)	4/9/2014	and this recor	d is true to th	e best of my	knowledg	e and b	oelief.		
	Kansas	Water Well C	ontractor's Licen	se No. 236	This water	well record wa	as completed	on (mo/d	day/yea	ır) 4	/11/2014	
	under th	e business na	ame of Harp	Well and Pump S	Service	by (s	ignature)		To	odd	S. Harp)