Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NWSW 1/4 21 Т 26 S R 1W E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 4754 N. Emerald Ct. Maize, Kansas **DEAN, Randy Construction** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 4065 N. Woodlawn #3 Belaire, Kansas CITY, STATE: ZIP CODE Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 45 ft. **ELEVATION:** Depth of groundwater Encountered: ft. ft ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/24/14 Pump test data: Well water was ft. after N₩ NE gpm Est. Yield: apm Well water was ft. after hours of pumping @ gpm Ξ Bore Hole Diameter 12 to 45 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only S₩ SE 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 5 CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 35 Blank casing diameter to ft.. Dia. ft.. in. to Dia in ft. 12 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 2. Brass 4. Galvanized Concrete Tile 10. Asbestos-Cement None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 45 From to ft.. From ft. to From ft. to ft.. From ft. **GRAVEL PACK INTERVALS:** 24 ft. to From ft.. From to ft. From ft to ft., From to ft. **GROUT MATERIALS:** 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. 24 ft., From ft. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit West How many feet? 10 ft. plus Direction from well? From Τо LITHOLOGIC LOG LITHOLOGIC LOG From To 0 topsoil 3 8 clay 35 fine sand 8 35 45 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 4-24-14 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp