VATER WELL RECORD	Form WV	VC-5	Divis		r Resources App. No	o	
LOCATION OF WATER WELL:	Fraction		Section	Number	Township No.	Range Number	
Communick	1/4 1/4 NW	1/4 SE 11/4		30	T 26 S	R 1 □E ☑W	
Street/Pural Address of Well Location:	if unknown, distance &	direction	Global F	Positioning	System (GPS) in	itormation:	
from nearest town or intersection: If at owner's address, check here .			Latitude: (in decimal degrees)				
11007 Hampton Lakes			Longitude: (in decimal degrees)				
Mairo KS 67101			Elevation:				
Maize, KS 67101			Datum: WGS 84, NAD 83, NAD 27				
2 WATER WELL OWNER: Moede	er Construction		Collection	on Method:			
RR#, Street Address, Box #: 4700 W. Irving			GPS unit (Make/Model:				
City, State, ZIP Code : Wichita, KS 67209			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
Violitic	1, 10 0,200		Est. Acc	uracy:	<3 m, 3-3 m,	3-13 III, >13 III	
SECTION BOX: Depth(s) Groun	COMPLETED WELL ndwater Encountered	(1).25	ft. halow le	(2) nd surface	measured on mo/o		
	ft after hours pumping gpm						
T ATTEL Hours pumping Spin							
[-1] = [NV - 1] = [ND - 1] $[NV - 1] = [NV - 1] = [N$							
TO DE LICED AC. Dublic water sinnly Licellia Injection wen							
The state of the s							
SW SE							
Was a chemical/bacteriological sample submitted to Department? Yes No							
i vo ii ii ii aan aa							
S If yes, mo	sinfected? Ves	No	••••				
5 TYPE OF CASING USED: Ste	eel PVC []	Other		••••••			
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .5							
				II., I	ialmace or gauge h	50R26	
Casing height above land surface!	× in., weight		lbs./IL.	, wan ui	ickliess of gauge i	10	
TYPE OF SCREEN OR PERFORATION	N MATERIAL:						
Ctool Ctoinless Steel	V I PVC	L] Other (5]	pecity)		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Brass Galvanized Steel	☐ None used (open n	iole)					
SCREEN OR PERFORATION OPENIN		7 Torch out	☐ Drill	led holes	☐ None (open he	ole)	
Continuous slot Mill slot Louvered shutter Key punched	. 🗆 ***********************************	Cour out	IIΩthe	er (snecity).			
☐ Louvered shutter ☐ Key punched SCREEN-PERFORATED INTERVALS							
GRAVEL PACK INTERVALS	: From ZU	ff to OU		. π., rrom		L. LU 10.	
	T	# to		TT Prom		L. LU	
6 GROUT MATERIAL: Neat cer	/ Compant arrays	+ D Dante	nite 🗀	l Other			
6 GROUT MATERIAL: Neat Co.	to 20 ft From	n	ft. to	ft	., From	ft. toft.	
Grout Intervals: From .3 ft. What is the nearest source of possible con	ntamination'						
What is the nearest source of possible con	lines Pit privy	Livestock		☐ Insectici		other (specify below)	
☐ Septic tank ☐ Lateral ☐ Sewer lines ☐ Cesspoo		☐ Fuel stora	ige [ed water well		
☐ Watertight sewer lines ☐ Seepag		Fertilizer	storage [Oil well/	'gas well		
Direction from well South		Distance	e from we	1118			
FROM TO LITHOLO	OGIC LOG	FROM	TO	LITHO.	LOG (cont.) <u>or</u> PI	LUGGING INTERVALS	
0 3 Topsoil							
		1					
		1					
20 60 Medium Sand		†					
		+	 				
			 				
			 				
			 				
			┼				
·		NI. This	ton	voc [7]	structed recon	structed, or nlugged	
7 CONTRACTOR'S OR LANDOWN under my jurisdiction and was complete							
under my jurisdiction and was complete	d on (mo/day/year) . ייִייִי	99/69/17	Descrit	ac comple	lefton (mo/dav/ve	ar) 05/12/2014	
						Alar	
under the business name ofPremier i	Pullip & Well Selvice,	Vand DRINT	olearly Ple	ase fill in his	nks and check the corr	ect answers. Send one copy to	
INSTRUCTIONS: Use typewriter or ball point	pen. <u>PLEASE PRESS FIRMI</u>	LI and FRINI	1000 SW 1	Jackson St S	uite 420 Toneka Ka	nsas 66612-1367.	
Kansas Department of Health and Envi Telephone 785-296-5524. Send one copy to W	Ironment, Bureau of Water, Of	etain one for vo	ur records.	Include fee o	f \$5.00 for each const	ructed well. Visit us at	
Telephone 785-296-5524. Send one copy to w	http://www.kdheks.g	ov/waterwell/in	dex html				
	The second secon						