WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick \mathbf{SW} 1W16 Т 26 S E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 8202 W. Mystic Lakes South Maize, Kansas STAVER, Brian WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 8202 W. Mystic Lakes South ZIP CODE: 67101 CITY, STATE: Maize, Kansas Application Number: 140 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ NW NE gpm Est. Yield: Well water was ft. after hours of pumping @ gpm gpm 12 to 140 Ξ Bore Hole Diameter and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering \sim 5. Public water supply 7. Lawn and garden only SE 1. Domestic 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well ; if yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC Blank casing diameter 5 120 ft.. Dia. ft.. in. to in. to Dia in to ft. 12 Casing height above land surface: in.. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel Fiberglass 9. ABS 2. Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 7. Torch cut 9. Drilled holes 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL 120 ft. 140 to ft., From From ft. to ft. ft. From to ft., From ft ft to **GRAVEL PACK INTERVALS:** 24 ft 140 to From ft.. From to ft From ft. to ft., From to ft. **GROUT MATERIALS:** 6 Other 1. Neat cement 2. Cement Grout bentonite hole plug 3. Bentonite Grout Intervals: From ft., From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 50 ft. plus LITHOLOGIC LOG LITHOLOGIC LOG From From Τо To 0 3 topsoil 3 8 clav 25 8 fine sand 25 135 medium sand 135 140 grey shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 7/11/14 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236

by (signature)

under the business name of Harp Well and Pump Service

Todd S. Harp