WATER WEL	L RECORD F	orm WW	C-5 K	SA 82a-1212			
1 LOCATION OF WATER WELL: FRACTION			ON NUMBER		IUMBER	RANGE NUM	BER
	SW 1/4 SE	1/4	26 29	T 26	S	R 1W	E/W
Distance and direction from nearest town or city street address of well if to							
3819 N. Lily Ct. Maize, Kan							
2 WATER WELL OWNER: LOVE, Mike Constr	uction				Board of Agri	culture, Division of Wat	er Resource
RR#,ST. ADDRESS,BOX #: P.O. Box 7	0.0				_		
CITY, STATE: Valley Center, Kans			CODE:		Application Num	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	TED WELL: 65			ELEVATION:			
N Depth of groundwater Er		ft.			ft.		ft.
WELL'S STATIC WATE			V LAND SU	RFACE MEASUR	ED ON mo/d	lay/yr: <b>2/19/1</b>	.5
1 1 11/2   1	test data: Well wat			ft. after		of pumping @	gpm
Est. Yield:  Bore Hole Diameter	gpm Well wat	_		ft. after		of pumping @	gpm
	12 in.	to <b>6</b> 5	5 ft.	and	in,	to	ft.
1 11222 1111211 10 22 1		ter supply <	7. Lawn a	nd garden only	9. Dewaterii	•	
	dustrial 6. Oil field w				10. Monitorin	12. Other (Spe ig well	city below)
	gical sample submitted to D		YES	NO	; If yes, v	vhat mo/day/yr was	sample
submitted			Was W	ater Well Disinfed	ted? (	YES NO	1
5 TYPE OF CASING USED: 5. Wrought Iro	n 7. Fiberglass	9. Oth	er (Specify	below) CASIN	IG JOINTS: (	Glued T	hreaded
1. Steel 3. RPM (SR)		s SDR	-26			Welded (	lamped
2. PVC 4. ABS 6. Asbestos-C		ie -					
Blank casing diameter 5 in. to 45	•	in.	to	ft., Di	<b>a</b> . i	in. to	ft.
Casing height above land surface: 12 in.,	Weight:	2.35 lbs	s. / ft.	Wall thick	ness or gaug	je No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)							
2. Brass 4. Galvanized 6. Concrete Tile	8. RMP (SR)	10. As	bestos-Cerr	nent 12. None	used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole						en hole)	
2. Louvered shutter 4. Key punched 6. Wir	e wrapped	8. Saw	cut	10. Other	(specify)		
SCREEN - PERFORATION INTERVAL From	<b>45</b> ft. to	65	ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From	<b>24</b> ft. to	65	ft.,	From	ft.	to	
From	ft. to		•				ft.
			ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to What is the nearest source of possible contamination:					ft.		
1. Septic tank 4. Lateral lines 7. Pit privy			pens	13. Insectici	secticide storage 15. Oil well/Gas well		well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below						ify below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage							
Direction from well? West	•		•	How man	/ feet? 10 f	t. plus	
From To LITHOLOGIC L	OG	From	To			GIC LOG	
0 3 topsoil							
3 14 clay							
14 35 fine sand		<u> </u>					
35 45 clay				·			
45 65 medium sand							
							w
		ļ					
						· · · · · · · · · · · · · · · · · · ·	
7					*		
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and							
was completed on (mo/day/year) 2/19/2015 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 236	This water we	ll record was	completed	on (mo/day/year)	2/23	/2015	
under the business name of Harp Well and Pump Service by (signature)							
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp							