WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: TOWNSHIP NUMBER FRACTION SECTION NUMBER RANGE NUMBER Sedgwick SE SW NE 27 26 S R 1W E/W 1/4 1/4 Т Distance and direction from nearest town or city street address of well if located within city? 6233 W. Kollmever Wichita, Kansas PATTERSON, Derek WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 6233 W. Kollmeyer CITY, STATE: Wichita, Kansas Application Number: ZIP CODE 40 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** 3 Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 14 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm Ξ Bore Hole Diameter 12 ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO YES Was Water Well Disinfected? (YES) NO submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 Blank casing diameter in. 30 ft... Dia. ft., Dia. ft. to in. to in. to 12 2.35 Wall thickness or gauge No. Casing height above land surface: in . Weight: lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 5. Gauzed wrapped 8. Saw cut 2. Louvered shutter 6. Wire wrapped 10. Other (specify) 4. Key punched 30 40 SCREEN - PERFORATION INTERVAL ft. From to ft.. From ft. ft. to From ft. to ft., From ft. ft. to 24 GRAVEL PACK INTERVALS: ft. to 40 From ft., From ft. to ft. ft. From to ft.. From to ft. **GROUT MATERIALS:** Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 24 From From ft., ft. ft.. ft. to From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit South How many feet? 40 ft. plus Direction from well? LITHOLOGIC LOG From LITHOLOGIC LOG From To Τо 0 3 topsoil 3 clay 6 15 lfine sand 6 15 40 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)

4/27/2015