WATER WELL R Original Record		n WWC-5 nge in Well U			ision of Water		Well ID		
1 LOCATION OF W.		Fraction			urces App. No. tion Number	Township Numb		ge Number	
County: Sec			e4 ne4	1/4	18	T Dus S	R R	DE X W	
2 · WELL OWNER: La	Name:	First:				ere well is located			
Business: direction from nearest town or intersection): If at owner's, address, check here:									
Address: () LM	Nuchol	5							
Address: OIM MICHOIS Address: City: State: ZIP: 4425 N. Ridge Rol. Wichita Ks.									
3 LOCATE WELL				-1 c 1	1	- VVW	my	101	
WITH "X" IN	4 DEPTH OF CO	MPLETEI) WELL:	ゴ.カ ft.	5 Latitude	<u>,</u>	((decimal degrees)	
SECTION BOX: Depth(s) Groundwater Encountered: 1)				tt.	tt. Longitude:(decimal degrees)				
2) ft. 3) ft., or 4) \(\subseteq WELL'S STATIC WATER LEVEL:				-					
*					Source for Latitude/Longitude.				
NW NE	□ above land surface, measured on (mo-day-yr Pump test data: Well water was				1	(WAAS enabled?			
					☐ Land Survey ☐ Topographic Map		٠,		
W E	after hours pumpingg				Online Mapper:				
SW SE	Well water was ft.								
	after hours pumping gr Estimated Yield:			gpm	6 Elevation:ft. Ground Level TOC				
S	Bore Hole Diameter:	in	to	. ft. and	Source:	☐ Land Survey ☐ (GPS 🗆 To	pographic Map	
1 mile	1	in.		_		Other		•••••	
7 WELL WATER TO	BE USED AS:								
1. Domestic:		Water Supply:			10. 🗌 Oil Fi	ield Water Supply: le	ease		
Household	6. Dewate								
Lawn & Garden		Recharge: wring: well ID				\square Uncased \square (mal: how many bores			
2. Irrigation		ntal Remedia				d Loop Horizont			
3. Feedlot	☐ Air Spa		Soil Vapor E			Loop Surface Di			
4. Industrial	☐ Recove		Injection			(specify):			
Was a chemical/bacter	iological sample sul	mitted to k	OHE?	Yes 🔀 No	If yes, date sa	imple was submitte	:d:		
Water well disinfected?		•				· ,			
8 TYPE OF CASING								l Threaded	
Casing diameter									
Casing diameter	in. 10	ft., Diameter		in. to	ft., Diamete	rin. to _p .	tt.		
Casing height above land s	surface	in. Weig	ht	in. to lbs./ft.	ft., Diamete Wall thicknes	ss or gauge No	o PST		
Casing height above land s TYPE OF SCREEN OR	PERFORATION M	in. Weigi ATERIAL:	ht	in. to lbs./ft.	Wall thickness	ss or gauge No	o PSJ		
Casing height above land s TYPE OF SCREEN OR ☐ Steel ☐ Stain	PERFORATION M less Steel	in. Weigl ATERIAL: berglass	ht	lbs./ft.	Wall thicknes	erin. toss or gauge No	o PSJ		
Casing height above land s TYPE OF SCREEN OR ☐ Steel ☐ Stain	PERFORATION Maless Steel	in. Weight ATERIAL: berglass oncrete tile	ht	in. to	Wall thicknes	ss or gauge No	o PSJ		
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	DUTFACE	in. Weight ATERIAL: berglass oncrete tile ARE: Gauze Wrapp	htPVC None us	sed (open hole	Wall thicknes	(Specify)	o.P.J.		
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter	DUTFACE	in. Weight ATERIAL: berglass oncrete tile ARE: Gauze Wrapp Wire Wrapp	ht	sed (open hole rch Cut D y Cut D	Wall thickness Other Other Orilled Holes Jone (Open Hole	Sor gauge No	o.P3J-		
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE	DUTFACE	in. Weight ATERIAL: berglass encrete tile ARE: Gauze Wrapp Wire Wrapp om	ht	sed (open hole rch Cut D y Cut D n ft., From.	Wall thickness Other Other Orilled Holes Jone (Open Hole	Sor gauge No	6. P.3.1		
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG	DURFACE	in. Weight ATERIAL: berglass oncrete tile ARE: Gauze Wrapp Wire Wrapporom	PVC None use ped Say ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From .	Wall thickness Other Orilled Holes Jone (Open Hole	Sor gauge No	ft. to	ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapp wom	PVC None use ped Sar ft. to Sar rout Be Bei	sed (open hole rch Cut D y Cut N ft., From ft., From .	Wall thickness Other Other Orilled Holes Jone (Open Hole ft. to Other	Sor gauge No	ft. to	ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapp wom	PVC None use ped Sar ft. to Sar rout Be Bei	sed (open hole rch Cut D y Cut N ft., From ft., From .	Wall thickness Other Other Orilled Holes Jone (Open Hole ft. to Other	Sor gauge No	ft. to	ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrappor Com	PVC None use ped Sar ft. to Sar rout Be Bei	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Jone (Open Hole ft. to Other	Sor gauge No	ft. to	ft. ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapperson	ped Too ft. to	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. cide Storage oned Water V	ft. ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line	PERFORATION Maless Steel	in. Weight ATERIAL: berglass uncrete tile ARE: Gauze Wrapp Wire Wrapp com Cement gft., From ines	ped Too ft. to	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Fine (Open Hole fine to the Other It, From Livestock Pens	Sor gauge No	ft. to ft. to ft. to	ft. ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line	PERFORATION Maless Steel	in. Weight ATERIAL: berglass uncrete tile ARE: Gauze Wrapp Wire Wrapp com Cement gft., From ines	ped Too ft. to	sed (open hole rch Cut D w Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole In to Other It to Other Livestock Pens Fuel Storage Fertilizer Storage	Ss or gauge No	ft. to ft. to ft. to ft. to ft. cide Storage oned Water Vell/Gas Well	ft. ft.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well?	PERFORATION Maless Steel	in. Weight ATERIAL: berglass concrete tile ARE: Gauze Wrapp Wire Wrapp com Cement g com ft., From ines l Pit Dist	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line	PERFORATION Maless Steel	in. Weight ATERIAL: berglass uncrete tile ARE: Gauze Wrapp Wire Wrapp com Cement gft., From ines	ped Too ft. to	sed (open hole rch Cut D w Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Ss or gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Lin Other (Specify) Direction from well?	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapp om	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp wire Wrapp om	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapp om	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 10 J 10 J	PERFORATION Maless Steel	in. Weight ATERIAL: berglass encrete tile ARE: Gauze Wrapp Wire Wrapp com	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 15 A O 20 30	PERFORATION Maless Steel Filanized Steel Contamination: Contaminatio	in. Weight ATERIAL: berglass encrete tile ARE: Gauze Wrapp Wire Wrapp com	ped Too ft. to	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 11 STAIR	PERFORATION Maless Steel	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp Wire Wrapper om	ped Too ft. to	sed (open hole rch Cut D y Cut N ft., From ft., From . ft. to	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 30 30 33 50	PERFORATION Maless Steel	in. Weight ATERIAL: berglass sucrete tile ARE: Gauze Wrapp Wire Wrappor Gom	ped Too ft. to	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Ione (Open Hole	Sor gauge No	ft. to ft. to ft. to ft. to cide Storage oned Water Vell/Gas Well	ft. ft. 	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 10 FROM TO 10 FROM TO 11 CONTRACTOR'S	PERFORATION Maless Steel Filanized Steel Control Opening Steel Control O	in. Weight ATERIAL: berglass encrete tile ARE: Gauze Wrapp Wire Wrapp om	PVC None use ped Too ed Sar ft. to Sar ft. to Sar rout Ber Pit Privy Sewage Lag Feedyard ance from we	sed (open hole rch Cut	Wall thickness Other Orilled Holes Flone (Open Hole fl. to Other It. to Other The From Livestock Pens Fuel Storage Fertilizer Storage TO LI	Other (Specify)	ft. to	well	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 10 FROM TO 10 FROM TO 11 CONTRACTOR'S	PERFORATION Maless Steel Filanized Steel Control Opening Steel Control O	in. Weight ATERIAL: berglass encrete tile ARE: Gauze Wrapp Wire Wrapp om	PVC None use ped Too ed Sar ft. to Sar ft. to Sar rout Ber Pit Privy Sewage Lag Feedyard ance from we	sed (open hole rch Cut	Wall thickness Other Orilled Holes Flone (Open Hole fl. to Other It. to Other The From Livestock Pens Fuel Storage Fertilizer Storage TO LI	Other (Specify)	ft. to	well	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 11 CONTRACTOR'S under my jurisdiction ar	PERFORATION Maless Steel Filanized Steel Control Opening Steel Control O	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp wire Wrapp om	PVC None use ped Too ed Sar ft. to Sar ft. to Sar rout Ber Pit Privy Sewage Lag Feedyard ance from we	sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Ione (Open Hole	Constructed, Trecorue to the best of m	ft. to	or □ plugged pe and belief.	
Casing height above land s TYPE OF SCREEN OR Steel Stair Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GRAVEL PAC GRAVEL PAC GRAVEL PAC GRAVEL PAC GRAVEL PAC From Material Sewer Line Other (Specify) Direction from well? 10 FROM TO 10 FROM TO 11 CONTRACTOR'S under my jurisdiction ar Kansas Water Well Con under the business name	PERFORATION Maless Steel Filanized Steel Contained Steel Con	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp wire Wrapp com	PVC None use ped Too ed Sar ft. to S. ft. to S. rout Beserved Pit Privy Sewage Lag Feedyard ance from we	Ibs./ft. sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Jone (Open Hole In to	Other (Specify)	ft. to	or plugged ge and belief.	
Casing height above land s TYPE OF SCREEN OR Steel Stain Brass Galv SCREEN OR PERFOR. Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAC GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank Sewer Lines Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO	PERFORATION Maless Steel Filanized Steel Control Opening Steel Control O	in. Weight ATERIAL: berglass soncrete tile ARE: Gauze Wrapp wire Wrappo om	PVC None use ped Too ed Sar ft. to Sar ft.	Ibs./ft. sed (open hole rch Cut	Wall thickness Other Other Orilled Holes Ione (Open Hole In to Other In to In to In to In the to	Son gauge No	ft. to ft. to	or plugged ge and belief.	