

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Sedgewick</u>		NE 1/4 SW 1/4 SE 1/4		21		T 24 S		R 1 EW			
Distance and direction from nearest town or city street address of well if located within city? <u>4823 N. Ridge Rd, Wichita, KS</u>											
2 WATER WELL OWNER: <u>Doyce Parish</u>											
RR#, St. Address, Box # : <u>4823 N. Ridge Rd</u>											
City, State, ZIP Code : <u>Wichita, KS</u>											
Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>90</u> ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. <u>37</u> ft. 2. <u>37</u> ft. 3. <u>37</u> ft.									
		WELL'S STATIC WATER LEVEL <u>37</u> ft. below land surface measured on mo/day/yr <u>3.9.98</u>									
		Pump test data: Well water was <u>WN</u> ft. after <u>WN</u> hours pumping <u>WN</u> gpm									
		Est. Yield <u>WN</u> gpm: Well water was <u>WN</u> ft. after <u>WN</u> hours pumping <u>WN</u> gpm									
		Bore Hole Diameter <u>10</u> in. to <u>90</u> in. and <u>90</u> in. to <u>90</u> in.									
		WELL WATER TO BE USED AS:									
		1 Domestic ☒ 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted									
		Water Well Disinfected? Yes ☒ No ☐									
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐ 2 PVC ☒ 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ 7 Fiberglass Threaded ☐											
Blank casing diameter <u>5</u> in. to <u>90</u> ft. Dia <u>14</u> in. to <u>160</u> lbs./ft. Wall thickness or gauge No.											
Casing height above land surface <u>14</u> in. weight <u>160</u> lbs./ft.											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC ☒ 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot ☒ 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS: From <u>80</u> ft. to <u>90</u> ft. From <u>80</u> ft. to <u>90</u> ft.											
GRAVEL PACK INTERVALS: From <u>30</u> ft. to <u>90</u> ft. From <u>30</u> ft. to <u>90</u> ft.											
6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite ☒ 4 Other											
Grout Intervals: From <u>80</u> ft. to <u>90</u> ft. From <u>80</u> ft. to <u>90</u> ft.											
What is the nearest source of possible contamination:											
1 Septic tank ☒ 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? <u>South</u> How many feet? <u>70 FT</u>											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		2		TOPSOIL							
2		36		Clay							
36		67		med sand							
67		76		Clay							
76		90		med sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3.9.98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>611</u> This Water Well Record was completed on (mo/day/yr) <u>3.9.98</u> under the business name of <u>Chase Drilling</u> by (signature) <u>D. Chase</u>											