WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: County: Sedgwick	Fraction 1/4 SE 1/4 NW 1/4 SW	Section Number Township No. Range Number
Street/Rural Address of Well Location;	if unknown distance & direction	Global Positioning System (GPS) information:
from nearest town or intersection. If at	owner's address check here	Latitude: (in decimal decrees)
4045 LC	lkeridge St 6720	Longitude:
10-13 2	wekinds of old	Elevation:
		Datum: ☐ WGS 84, ☐ NAD 83, ☐ NAD 27
	r Construction	Collection Method:
RR#, Street Address, Box #: 4700 W		GPS unit (Make/Model:)
City, State, ZIP Code : Wichita	, KS 67209	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m
3 LOCATE WELL		
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 60	ft.
SECTION BOX: Denth(s) Groun	dwater Encountered (1) 20	ft. (2) ft. (3) ft.
N WELL'S STATIC WATER LEVEL. 20 ft. below land surface measured on mo/day/yr		
Pump test data: Well water was		
EST. YIELD. 18gpm. Well water was		
W E Bore Hole Diameter 1.9in. toft., andin. toft.		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SW A SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)		
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted		
mile Water well disinfected?		
,		
5 TYPE OF CASING USED: Steel PVC Other		
Casing diameter .5		
Casing diameter in. to it., Diameter in. to it., Diameter in. to it. Casing height above land surface. 12 in., Weight 2.5 lbs./ft., Wall thickness or gauge NoSDR26		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
Steel Stainless Steel		Other (Specify)
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:		
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 20		
From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft., From ft. to ft.		
From ft. to ft., From ft. to ft.		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other		
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other		
What is the nearest source of possible cont	amination:	
	nes Pit privy Livesto	
Sewer lines Cesspool	Sewage lagoon Fuel sto	
☐ Watertight sewer lines ☐ Seepage p Direction from well North	oit Feedyard Fertiliz	re storage
FROM TO LITHOLOG		
0 3 Topsoil	TROM	TO DITTIO. EGG (CORE.) OF T EGGGRAG THAT ERROTTES
3 20 Clay	• .	
20 - 60 Medium Sand		
	·	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) .6/9/2015 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 238 This Water Well Record was completed on (mo/day/year) 6/9/2015		
under the business name of		
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.		
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		
http://www.kdhebe.gov/waterwell/index.html		