WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NW1/4 NW1/4 1/4 30 Т 26 S R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 4127 N. Rutgers Circle Maize, Kansas WATER WELL OWNER: ROBL CONSTRUCTION Board of Agriculture, Division of Water Resource "RR#,ST. ADDRESS,BOX #: 5842 W. 21st N. Wichita Kansas CITY, STATE: ZIP CODE Application Number: 70 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 22 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data Well water was ΝW NE ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm ≣ Bore Hole Diameter 12 70 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4 Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES submitted NO Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Clued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 **50** Blank casing diameter to Dia. ft., Dia. in. to in. to ft. 12 2.35 Casing height above land surface: in Weight: lbs. / ft Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 50 70 ft. to ft.. From ft ft to ft. From to ft., From ft. ft. to 24 GRAVEL PACK INTERVALS: ft. to 70 From ft., From ft. to From ft. to From ft to ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft.. ft to ft From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13 Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? Southeast How many feet? 50 ft. plus From From Τo LITHOLOGIC LOG To LITHOLOGIC LOG topsoil 21 clav 21 37 fine sand 37 clay 42 42 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and 11/25/15 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/30/15

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb