WATER	WELL RECORD	Form WWC	-5	Division of Water	Resources App. No	, L	
	TION OF WATER WELL:	Fraction		Section Number	Township No.	Range Number	
	: Sedgwick	1/4 NW 1/4 NW 1/4		28	T 26 S	R 1 DE WW	
	Rural Address of Well Location;	Global Positioning					
from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees)			
8715 W. Candlewood St. Wichita, Ks 67235				Longitude: (in decimal degrees) Elevation:			
				Datum: WGS 84	□ NAD 93 □	 NAD 27	
		Construction		Collection Method:	, 🗀 IAAD 63, 🗀	NAD 21	
RR#, Street Address, Box #: 4700 W. Irving				GPS unit (Make/Model:)			
City, S	tate, ZIP Code : Wichita	. KS 67209				Map, Land Survey	
Est. Accuracy: 3 m, 3-5 m, 5-15 m, >15 m							
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40 ft.							
		DX: Depth(s) Groundwater Encountered (1).10 ft. (2) ft. (3)					
	N WELL'S STAT	WELL'S STATIC WATER LEVEL10ft. below land surface measured on mo/day/yr					
	Pump test data: Well water was						
NW.	EST. YIELD. 18gpm. Well water was						
w	w E Bore Hole Diameter 10in. to .40ft., andin. toft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SW Onestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
Water were distincted. E. 163							
5 TYPE OF CASING USED: Steel PVC Other Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter 5							
Casing height above land surface12							
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From 20							
From							
G	RAVEL PACK INTERVALS:	From . 20 ft. to	40	ft., From	ft. 1	to ft.	
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft., From ft.							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well							
Directio	on from well South			om well25'			
FROM '	TO LITHOLOG	IC LOG FR	OM	TO LITHO. LC	G (cont.) or PLU	GGING INTERVALS	
0 10							
10 - 20							
20 30							
30 3				· ·			
32 40	D Equus Sand						
					·		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .8/12/2015 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 238 This Water Well Record was completed on (mo/day/year) 8/13/2015							
under the b	usiness name of Premier Pur	np. & Well Service, Inc.		by (signature V.V.)	Dage 1	3.16	
INSTRUCTI	ONS: Use typewriter or ball point pen	. PLEASE PRESS FIRMLY and I	PRINT clear	dy. Please fill in blanks a	and check the correct a	inswers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit its at							