Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NW1/4 NW1/4 33 Т 26 s R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 3609 N. Pepper Ridge Wichita, Kansas KLAUSMEYER CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 10008 W. York ZIP CODE: 67215 Wichita, Kansas CITY, STATE: Application Number: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 65 **ELEVATION:** ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/14/15 Pump test data: Well water was ft. after -MW gpm ΝE Est. Yield: gpm Well water was ft. after hours of pumping @ apm Ξ Bore Hole Diameter 12 to 65 and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 5. Public water supply 7. Lawn and garden only 1 Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 Blank casing diameter to 45 ft., Dia. ft.. Dia. in. in to in. ft. to 12 2.35 Wall thickness or gauge No. Casing height above land surface: Weight: lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9. ABS 11. Other (specify) 5. Fiberglass 1. Steel 2. Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 45 ft 65 ft., From to From ft to ft. From to ft., From 24 **GRAVEL PACK INTERVALS:** to 65 ft.. From ft From to ft From to ft., From to ft. 6 **GROUT MATERIALS:** Other bentonite hole plug 2 Cement Grout 1 Neat cement 3. Bentonite 4 ft Grout Intervals: 24 From ft.. From ft. to ft.. From ft. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 2. Sewer lines 5. Cess Pool 14. Abandon water well 12. Fertilizer storage 9. Feed yard 3 Watertight sewer line 6. Seepage pit How many feet? 40 ft. plus Direction from well? South LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τo 0 3 topsoil 18 clay 3 fine sand 18 45 45 65 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or under my jurisdiction and

was completed on (mo/day/year) 9/11/2015 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/14/2015 Todd S. Harb under the business name of Harp Well and Pump Service by (signature)