WATER WELL RECORD I	Form WV	VC-5 K	SA 82a-1	212		
1 LOCATION OF WATER WELL: FRACTION		TION NUMBER	1	TOWNSHIP NUMBER RANGE NUMBER		
Sedgwick SE 1/4 NE 1/4 SW	1/4	31	<u> </u>	26 S	R 1W	⁷ E/W
Distance and direction from nearest town or city street address of well if located within city? 3238 N. Shefford Wichita, Kansas						
2 WATER WELL OWNER: ROBL CONSTRUCTION						
RR#,ST. ADDRESS,BOX #: 5842 W. 21st N.				Board of Agr	riculture, Division of W	ater Resource
CITY, STATE: Wichita, Kansas		IP CODE:		Application Nu	mber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 7	0 ft.		ELEVATION	l:		
Depth of groundwater Encountered:	ft			ft.		ft.
WELL'S STATIC WATER LEVEL 35	FT. BELC	W LAND SU	RFACE MEA	SURED ON mo/	day/yr: 1/28	/16
Pump test data: Well wa	ter was		ft. after	hour	s of pumping @	gpm
≔	eter was	70 .	ft. after		s of pumping @	gpm
WELL WATER TO BE USED AS:	to 7	7 0 ft.	and	in.	to	ft. tion well
	ater supply	7. Lawn a	nd garden o	9. Dewater	ing 12. Other (Sp	
2. Irrigation 4. Industrial 6. Oil field v	vater supply	8. Air con	ditioning	10. Monitori	ng well	
S Was a chemical/bacteriological sample submitted to submitted	Department?	YES	NO Vater Well Dis		what mo/day/yr w	as sample IO
5 TYPE OF CASING LISED:					\succ	
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass	•	ther (Specify	below) C	ASING JOINTS:	Glued Welded	Threaded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete 6	ile SD	R-26				Olampea
Blank casing diameter 5 in. to 50 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight:	2.35 II	bs. / ft.	Wal	thickness or gau	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. A			Other (specify)	. 1 1	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. A	sbestos-Cen	nent 12.	None used (open	nole)	
SCREEN OR PERFORATION OPENINGS ARE:	 .		0 B		44 Nama (=	6 - 1 - 1
1. Continuous slot 3. Mill slot 5. Gauzed wrapped		orch cut		rilled holes	11. None (o	pen noie)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Sa	w cut	10. C	ther (specify)		
SCREEN - PERFORATION INTERVAL From 50 ft. to	70	ft.,	From	ft.	to	ft.
From ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From 24 ft. to	• 70	ft.,	From	ft.	to	ft.
From ft. to)	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	;	3. Bentonite		Other bent	tonite hole plu	g
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	ft.	to	ft.,	From	ft. to	ft.
	10. Livestoc	k pens	13. Inse	cticide storage	15. Oil well/G	as well
	11. Fuel sto	rage	14. Aba	ndon water well	16. Other (sp	ecify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilize	r storage				
Direction from well? West			How	many feet? 10	ft. plus	
From To LITHOLOGIC LOG	From	То		LITHOLO	OGIC LOG	
0 3 topsoil	}					
3 25 clay 25 50 fine sand	<u> </u>					
50 70 medium sand						
	 	ļ				
	+					
	 	 				
	 	 	- FUEL			
Contractor's or Landowner's Certification: This water well was 1. constructed	2. re	constructed	or 3.	plugged	under my jurisdiction	on and
was completed on (mo/day/year) 1/28/2016 and this record	is true to the	e best of my k	nowledge an	d belief.		
Kansas Water Well Contractor's License No. 236 This water w	ell record wa	s completed	on (mo/day/v	ear) 2/	1/16	
under the business name of Harp Well and Pump Service	by (si	gnature)	7		Harb	