WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER FRACTION TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE NE 1/4 1/4 31 Т 26 S R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 11331 W. Fontana Circle Wichita, Kansas WATER WELL OWNER: **SHARP HOMES** Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2131 Collective #A Wichita, Kansas CITY, STATE: ZIP CODE Application Number: 70 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. N ft. 30 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 1/21/16 Pump test data: Well water was NW NE ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ξ 12 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 5. Public water supply 7. Lawn and garden only 1. Domestic 3. Feedlot 12. Other (Specify below) 2. Irrigation 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 5 50 Dia. in. to ft., Dia ft. in 12 Casing height above land surface: in Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 50 ft. 70 to ft., From ft. ft. From to ft.. From ft ft. to 24 GRAVEL PACK INTERVALS: ft. 70 From to ft., From ft. ft. From ft. to ft.. From ft. ft. **GROUT MATERIALS:** Other bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft., From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit Direction from well? South How many feet? 10 ft. plus From Tο LITHOLOGIC LOG From Τo LITHOLOGIC LOG topsoil clay 20 20 fine sand medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

1/21/2016 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/22/16

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb