WATER WELL RECORD Form WWC-5 KSA 82a-1212 SECTION NUMBER 1 LOCATION OF WATER WELL: FRACTION TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE NW33 1W 1/4 1/4 T 26 E/W S R Distance and direction from nearest town or city street address of well if located within city? 3566 N. Lakeridge Ct. Wichita, Kansas WATER WELL OWNER: GONZALES, Michael Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX # 3566 N. Lakeridge Ct. Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 65 3 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered ft ft. 28 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 5/24/16 Pump test data: Well water was ft. after hours of pumping @ ·WW ΝE gpm Est. Yield: Well water was ft. after hours of pumping @ gpm gpm ≌ 12 65 Bore Hole Diameter and ft. WELL WATER TO BE USED AS 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1 Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial : If ves. what mo/day/vr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 45 Dia. ft . Dia Blank casing diameter in. to in to ft. Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3 Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 8. Saw cut 10. Other (specify) 2. Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL to ft., From ft From to ft From ft. to ft., From ft ft to GRAVEL PACK INTERVALS: 24 ft. to From ft.. From to ft. to ft., From From to ft. **GROUT MATERIALS:** Other 6 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: 24 ft.. From From ft. ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τo From Τо 3 topsoil 15 clay 15 40 fine sand 40 65 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and plugged 5/24/16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief This water well record was completed on (mo/day/year) 5/25/2016 Kansas Water Well Contractor's License No. 236

by (signature)

under the business name of Harp Well and Pump Service

Todd S. Harb