			WATER	WELL B	FCO	SD E	orm WV	NC-5 K	(SA 82a-12	012		
4 LOCATIO	ON OF WATE	D WELL.	FRACTION	VV LLL IN		<u> </u>		TION NUMBE		IIP NUMBER	BANCE	HIMPED
Sedg		R WELL:		1/4 NE	1/4	NW	1/4	30	1	26 S	RANGE I	
	d direction from	m nearest town or city st		well if located		y?						
	ER WELL C		USMEYE			TION						·
	ADDRESS		W York	K CONSI	KUC	ПОП				Board of Agric	culture, Division of	Water Resource
KK#,OT.			ita, Kansa	S			7	IP CODE:		Application Num	ber:	
3 LOCAT	E WELL'S LO		EPTH OF CO		VFII:	70		ii OODL.	ELEVATION:		501.	
WITH A	N "X" IN SEC	CTION BOX:	th of groundw				ft			ft.		ft.
	$\frac{1}{\sqrt{N}}$	i '	LL'S STATIC			25			LIDEACE MEAG	SURED ON mo/d		1/16
	1		LLSSIAIIC	Pump test da		Well wat		W LAND S	ft. after		-,,	
	NW -	·· NE· -	Est. Yield:	gpm	ala.	Well wa			ft. after		of pumping @ of pumping @	gpm gpm
Wile w		E Bo	re Hole Diame		2 in			70 ft		in.	to	ft.
-		1 1 -	LL WATER TO			•		, ,			44 1.1	ection well
,	sw -		Domestic	3. Feedlot		ublic wa	ter supply	7. Lawn	and garden on	9. Dewaterir	.9	Specify below)
	l	2.	Irrigation	4. Industria	al 6. C	Oil field w	ater supply	8. Air co	nditioning	10. Monitorin		, , , , , , , , , , , , , , , , , , , ,
'	s	1	as a chemical/ba	acteriological sa	ample sui	bmitted to D	Department?	YES	NO		hat mo/day/yr	
			mitted					Was	Water Well Disi	nfected? (YES	NO
9		SING USED:	5. Wrou	ight Iron	7. F	iberglass	9. O	ther (Specif	y below) CA	SING JOINTS: C	Glued	Threaded
	. Steel	3. RPM (SR)		stos-Cement	8 0	oncrete ti	sD	R-26			Welded	Clamped
	2. PVC	> 4. ABS										
Blank cas	sing diamete	er 5 in	n. to	48 ft	••	Dia.	in.	to	ft.,	Dia. i	n. to	ft.
Casing h	eight above	land surface:	12 in.	,	We	eight:	2.35	bs. / ft.	Wall	thickness or gaug	e No214	1
		OR PERFORATION I				<u> </u>				NII (
1. Stee		s. Stainless Steel	Fibergla		7. P\		9. A			Other (specify)		
2. Bras	ss 4	. Galvanized	6. Concret	te Tile	8. RI	MP (SR)	10. A	sbestos-Ce	ment 12. N	lone used (open l	nole)	
SCREEN	OR PERFO	RATION OPENINGS	S ARE:									
1. Conti	nuous slot	3. Mill slot	t	5. Gauzed v	rapped	ı	7. T o	rch cut	9. Dr	illed holes	11. None (open hole)
2. Louve	ered shutte	r 4. Key pur	nched	6. Wire wra	ped		8. S a	w cut	10. Ot	her (specify)		
SCREEN -	PERFORA	TION INTERVAL	From	48	ft.	to	70	ft.,	From	ft,	to	ft.
			From		ft.	to		ft.,	From	ft.		ft.
G	RAVEL PA	CK INTERVALS:	From	24	ft.	to	70	,			to	
	RAVELFA	CK INTERVALS.		24	ft.	to		ft.,	From	ft.	to	ft.
a L CBOI	JT MATERI	ALC:	From					ft.,	From	ft.	to	ft.
<u> </u>		1. Neat C			nent Gr	_		3. Bentonite			onite hole pl	•
	Intervals: e nearest so			to 24	ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy						0. Livestoo	k pens	13. Inse c	ticide storage	15. Oil well/	Gas well	
,						1. Fuel sto	rage	14. Aban	don water well	16. Other (s	pecify below)	
	rtight sewe	_		9. Feed ya	rd	1	2. Fertilize	r storage				
	from well?	Northeast	o p.t						How n	nany feet? 10 f	t. plus	
From	То	L	ITHOLOG	GIC LOG			From	То	<u> </u>	LITHOLO		*************************************
0	3	topsoil										
3	20	clay										
20	40	fine sand										
40	70	medium sand										
								-				
	1											
							-					
				•								

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6-21-16 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/22/16

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp