		WATER WE	ELL RECORE	D Forr	n WW	C-5 K	SA 82a-121	2			
1 LOCATION OF WAT	ER WELL:	FRACTION			SECTI	ION NUMBER	TOWNSHIP	NUMBER	RANGE NUM	IBER	
Ledgwick		SE 1/4	SW 1/4	SW 1/	4	27	Т 26	i s	R 1W	E/W	
Distance and direction from nearest town or city street address of well if located within city?											
3807 N. Estancia Wichita, Kansas											
2 WATER WELL		CLELLAN E		ES INC.							
RR#,ST. ADDRES	S,BOX #: 1108 W. 34th N.						Board of Agriculture, Division of Water Resource				
CITY	CITY, STATE: Wichita, Kansas ZIP CO						DE: Application Number:				
3 LOCATE WELL'S		DEPTH OF COMPL	FTED WELL:	40	ft.		ELEVATION:				
WITH AN "X" IN SI	ECTION BOX:				ft.			ft.		ft.	
N N		epth of groundwater		12 FT					7/10/		
	, vv	VELL'S STATIC WAT				N LAND SU	IRFACE MEASU				
NW	NE			Vell water w			ft. after		of pumping @	gpm	
A He		Est. Yield:	10	Well water v		• •	ft. after		s of pumping @	gpm	
		Bore Hole Diameter			to 4	0 ft.	and	in.	to	ft.	
		VELL WATER TO BE	E USED AS:	blic water	-upply (7 Lawn a	nd garden only	9. Dewaterii	•		
		- SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
		2. Irrigation 4. 1 Was a chemical/bacteri				VES	NO		what mo/day/yr wa	s sample	
S		was a chemical/bacteri ubmitted	IOIOgical sample such				Vater Well Disinfe		YES NO		
5 TYPE OF CA	ASING USED:				9.0#	her (Specify		ING JOINTS: (Glued T	Threaded	
1. Steel	3. RPM (S	5. Wrought I SR)	Iron 7. Fib	erglass			Delow) Cha	NG JOINTO.	\smile	Clamped	
2. PVC	> 4. ABS	6. Asbestos	-Cement 8. Cor	ncrete tile	SDR	L-26			Weided	Clampos	
Blank casing diame		in. to	25 ft., D	Dia.	in.	to	ft., [Dia.	in. to	ft.	
	_	10	,				-				
Casing height abo			Weig	ght: 2. 3	ט כנ	s. / ft.	Waltun	ckness or gaug	ge No214		
_	I OR PERFORATIO 3. Stainless Steel	N MATERIAL: 5. Fiberglass	7. PVC		9. AE	20	11. Oth	ner (specify)			
1. Steel		•							hale)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERF	ORATION OPENIN										
1. Continuous sl	ot 3. Mills	slot 5. G	Sauzed wrapped		7. Torch cut 9. Drilled holes 11. None (open hole)						
2. Louvered shut	ter 4. Key p	punched 6. W	Vire wrapped	(8. Sav	w cut	10. Othe	er (specify)			
		-	25 ft.	to	40		F				
SCREEN - PERFOR	RATION INTERVAL			to	40	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL P	ACK INTERVALS:	From	24 ft.	to	40	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MATE	RIALS: 1 Neat	t cement	2. Cement Gro		3	Bentonite		Other hent	onite hole plug		
Grout Intervals:	From 4		• •	From	ft.			From	ft. to	5 ft.	
3	source of possible of	contamination:	,			to	ft.,	From	Π. LŲ	п.	
1. Septic tank	4. Latera	7	. Pit privy	10. L	ivestoc	c pens	13. Insection	cide storage	15. Oil well/Ga	s well	
2. Sewer lines	5. Cess	Pool 8.	Sewage lagoon	11. F	Fuel stor	age	14. Abando	on water well	16. Other (spec	cify below)	
			Feed yard	12.	Fertilizer	storage					
3. Watertight sev		age hir	,,				How ma	iny feet? 10 f	ft, plus		
From To		LITHOLOGIC	10G		rom	To			GIC LOG		
0 3	topsoil	LITIOLOGIC	/100		10.11			LIIIIOLU			
$\frac{1}{3}$ 11	clay										
11 24	fine sand										
24 40	medium san	d									
7 Contractor's o	r Landowner's Certi	ification: This water	well was 1. cons	structed	2. rec	constructed	1 or 3. I	plugged	under my jurisdictio	n and	
was completed of	n (mo/day/year)	7/19/16	and this	record is tr	ue to the	best of my	knowledge and b	elief.			
			Thick	water well r	poord way			-) 7/3	20/16		
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourp											