


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 NW 1/4 SW 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
11314 W. Fontana Circle Wichita, Kansas

2 WATER WELL OWNER: SHARP HOMES	Board of Agriculture, Division of Water Resource
RR#.ST. ADDRESS, BOX #: 2131 N. Collective Ste #A	Application Number:
CITY, STATE: Wichita, Kansas	ZIP CODE:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 70 ft.	ELEVATION:
	Depth of groundwater Encountered: ft.	ft.
	WELL'S STATIC WATER LEVEL: 30 FT. BELOW LAND SURFACE MEASURED ON 9/2/16	mo/day/yr:
Pump test data:	Well water was ft. after hours of pumping @ gpm	
Est. Yield:	gpm Well water was ft. after hours of pumping @ gpm	
Bore Hole Diameter 12 in.	to 70 ft.	and in. to ft.
WELL WATER TO BE USED AS:	1. Domestic	2. Irrigation
3. Feedlot	4. Industrial	5. Public water supply
6. Oil field water supply	7. Lawn and garden only	8. Air conditioning
9. Dewatering	10. Monitoring well	11. Injection well
12. Other (Specify below)	Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted	
Was Water Well Disinfected? YES NO		

5 TYPE OF CASING USED:	1. Steel	2. PVC	3. RPM (SR)	4. ABS	5. Wrought Iron	6. Asbestos-Cement	7. Fiberglass	8. Concrete tile	9. Other (Specify below)	CASING JOINTS: Glued	Threaded	
Blank casing diameter	5 in.	to 40 ft.,	Dia.	in.	to ft.,	Dia.	in.	to ft.	Weight: 2.35 lbs. / ft.	Wall thickness or gauge No. .214	Clamped	
Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:	1. Steel	2. Brass	3. Stainless Steel	4. Galvanized	5. Fiberglass	6. Concrete Tile	7. PVC	8. RMP (SR)	9. ABS	10. Asbestos-Cement	11. Other (specify)	12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	1. Continuous slot	2. Louvered shutter	3. Mill slot	4. Key punched	5. Gauzed wrapped	6. Wire wrapped	7. Torch cut	8. Saw cut	9. Drilled holes	10. Other (specify)	11. None (open hole)	
SCREEN - PERFORATION INTERVAL	From	40 ft.	to	70 ft.,	From	ft.	to	ft.	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24 ft.	to	70 ft.,	From	ft.	to	ft.	From	ft.	to	ft.

6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other bentonite hole plug
Grout Intervals:	From 4 ft.	to 24 ft.,	From ft.	to ft., From ft. to ft.
What is the nearest source of possible contamination:	1. Watertight sewer line	2. Sewer lines	3. Septic tank	4. Lateral lines
5. Cess Pool	6. Seepage pit	7. Pit privy	8. Sewage lagoon	9. Feed yard
10. Livestock pens	11. Fuel storage	12. Fertilizer storage	13. Insecticide storage	14. Abandon water well
15. Oil well/Gas well	16. Other (specify below)	Direction from well? Southwest		

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	20	clay			
20	45	fine sand			
45	70	medium sand			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/2/2016 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/6/2016
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp