	WATER WELL RE	CORD F	orm WW	/C-5 K	SA 82a-1212	2			
1 LOCATION OF WATER WELL:	FRACTION		SECT	ION NUMBER	TOWNSHIP	NUMBER	RANGE NU	MBER	
Sedgwick	NW 1/4 NW	1/4 NE	1/4	34	T 26	S	R 1W	E/W	
Distance and direction from nearest town or city	street address of well if located wi	ithin city?							
North of 3723 N. Sienna Lakes Wichita, Kansas									
2 WATER WELL OWNER: MUI	LLIN CONSTRUCTI	ON LLC							
	S,BOX #: P.O. Box 529 Board of Agriculture, Division of Water Resource							ater Resource	
CITY, STATE: Wich	Y, STATE: Wichita, Kansas ZIP CODE: AP						plication Number:		
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETED W	FLL: 50	ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX:			ft.			ft.		ft.	
	pth of groundwater Encounter								
	WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 9/2/16							10	
							of pumping @	gpm	
В м — Е В	Est. Yield: gpm	Well wate		•	ft. after		of pumping @	gpm	
	Bore Hole Diameter 12		to 5	0 ft.	and	in.	to	ft.	
	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 1. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 1. Domestic 3. Feedlot 5. Public								
	If yes what mo/day/yr was sample								
	was a chemical/bacteriological san	nple submitted to D	epartment?	YES Was W	NO Vater Well Disinfe		YES N		
5 TYPE OF CASING USED:							Glued	Threaded	
1. Steel 3. RPM (SI	5. Wrought Iron R)	7. Fiberglass		her (Specify	Delow) CASI	NG JOINTS: (
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete til	e SDF	R-26			weided	Clamped	
Blank casing diameter 5	in. to 30 ft.,	Dia.	in.	to	ft., D	ia.	in. to	ft.	
	12							ic.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION		7.01/0	0.41	20	11 Oth	or (coocify)			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open h						pen hole)			
2. Louvered shutter 4. Key p	unched 6. Wire wrap	ped	8. Sa	w cut	10. Other	r (specify)			
						(
SCREEN - PERFORATION INTERVAL	From 30	ft. to	50	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	50	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					-				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:							ft.		
7 Bit private 10 Livestock pens 12 Insecticide storage 15 Oil well/Cas well							as well		
1. Septic tank 4. Lateral lines 8. Seware largoon 11. Fuel storage 14. Abandan water well 16. Other (specify below)									
2. Sewer lines 5. Cess Pool									
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? Southeast How many feet? 50 ft. plus									
Direction from wein			From	Tall					
	LITHOLOGIC LOG		From	То		LITHOLU	GIC LOG		
0 3 topsoil									
3 35 fine sand 35 50 medium sand									
35 50 medium sand									
1									
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 9/2/2016 and this record is true to the best of my knowledge and belief.									
				-	•		0017		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/6/2016									
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourd									