WATER WELL R		WWC-5		ivision of Water				
Original Record		ge in Well Use		sources App. No.		Well ID		
1 LOCATION OF WATER WELL:		Fraction		ection Number	Township Numb		ge Number	
County: SEDGWIC	NW1/4 NE1/4 SE1/4		12	T 26 S		□E■W		
2 WELL OWNER: Last Name:  Business: LARIAT CONSTRUCTION  Address:  Address: 9718 W 18TH CT N  Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:  6318 N RICHMOND ST								
City: WICHITA State: KS ZIP: 67212 VVICHITA, NS 67204								
3 LOCATE WELL WITH "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL:50						(decimal degrees)	
WELL'S STATIC WATER LEVEL:				ft. 02/2016 Source for Latitude/Longitude:  GPS (unit make/model:)				
w sw se x	Pump test data: Well waterhours	☐ Land	☐ Land Survey ☐ Topographic Map ☐ Online Mapper:					
s	Estimated Yield:20 gpm				6 Elevation:			
7 WELL WATER TO BE USED AS:								
1. Domestic:		ater Supply: well ID	••••••		ield Water Supply: 1	ease	•••••	
☐ Household	6. Dewaterin	•••••	11. Test Ho	11. Test Hole: well ID				
Lawn & Garden 7. Aquifer Recharge: well ID				☐ Case	☐ Cased ☐ Uncased ☐ Geotechnical			
☐ Livestock  2. ☐ Irrigation  8. ☐ Monitoring: well ID					12. Geothermal: how many bores?			
3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor Extr					b) Open Loop  Surface Discharge  Inj. of Water			
4. Industrial	☐ Recovery			13.  Othe	(specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:								
Water well disinfected? ■ Yes □ No								
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other								
Casing diameter 5 in. to 50 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to 50 ft., Casing height above land surface 12 in. Weight lbs./ft. Wall thickness or gauge No. SDR-26								
Casing height above land surface								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From .30 ft. to .40 ft., From								
GRAVEL PACK INTERVALS: From								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other  Grout Intervals: From								
□ Septic Tank □ Lateral Lines □ Pit Privy □ Livestock Pens □ Insecticide Storage								
Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well								
■ Watertight Sewer Lines								
☐ Other (Specify)								
	I IPHOLO	Distance from w					DIFFERMATO	
	LITHOLOG OP SOIL	SIC LUG	FROM	10 L	THO. LOG (cont.) or	PLUGGING	INTERVALS	
	LAY		+			,		
	INE SAND		<del> </del>	<del></del>				
	RAVEL		<del>-  </del>					
	LAY		1					
	<del></del>							
	·		Notes:					
44. 60. 770. 40. 60. 4. 4. 70. 70. 70. 70. 70. 70. 70. 70. 70. 70								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .08/02/2016 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No. 884 This Water Well Record was completed on (mo-day-year) .08/03/2016  under the business name of WENINGER DRILLING, LLC								
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St.	, Suite 420, Topeka, Kansas	66612-1367. Mail one to	Water Well O	wner and retain one				
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015								