CORRECTE P 1 1881 11 11 11 11 11 11 11 11 11 11 11								
WATER WELL RECORD Form WWC-5 1320411 Division of Water								
Original Record  1 LOCATION OF V	<u> </u>			urces App. No.	Township Numb	Well ID er Range Number		
County: Sedgwic		NE ¼ NE ¼	- 1	32	T 26 S	R 1 □ E ☑ W		
2 WELL OWNER: Last Name: RICHARDSOI First: KURT W/AF Street or Rural Address where well is located (if unknown, distance and								
Business: 7540 W Northward 5+ direction from nearest town or intersection): If at owner's address, check here: Address: 3728NTYLERGT Ste 200 Common 5 area Detween 3726/3726+								
Address:   2720/3722   T. V. C. + 67205								
2 LOCATE WITH								
WITH "X" IN	WITH "X" IN  4 DEPTH OF COMPLETED WELL:							
SECTION BOX:	2)							
	WELL'S STATIC WATER LEVEL:							
below land surface, measured on (mo-day-yr)								
	Pump test data: Well water was ft.				☐ Land Survey ☐ Topographic Map ☐ Online Mapper:			
1 1 1 1 1								
SW SE	after hours pumpi	ng		6 Florestia	1348 fr	Ground Level C TOC		
Estimated Yield:20gpm  Bore Hole Diameter:12 in. to60 ft. and				6 Elevation: 1348				
1 mile  Bore Hole Diameter:								
7 WELL WATER TO BE USED AS:								
1. Domestic:	Domestic: 5. ☐ Public Water Supply: well ID					10. Oil Field Water Supply: lease		
✓ Lawn & Garden	Z Lawn & Garden 7. ☐ Aquifer Recharge: well ID			Cased Uncased Geotechnical				
☐ Livestock 8. ☐ Monitoring: well ID								
3. Feedlot Air Sparge Soil Vapor Ex				· · · · · · · · · · · · · · · · · · ·				
4. ☐ Industrial ☐ Recovery ☐ Injection 13. ☐ Other (specify):								
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☑ No If yes, date sample was submitted:								
8 TYPE OF CASINO	USED: ☐ Steel ☑ PVC ☐ O	ther	CASIN	IG JOINTS:	☑ Glued ☐ Clamped	I ☐ Welded ☐ Threaded		
Casing diameter 5 in to 60 ft., Diameter in to ft., Diameter in to ft., Diameter in to ft.  Casing height above land surface 16 in Weight 15s./ft. Wall thickness or gauge No. 26								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☑ PVC ☐ Other (Specify)								
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot ☑ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From .40 ft. to 60 ft., From ft. to ft.								
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage								
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well								
✓ Watertight Sewer Lines								
				TO LI	ft.	PLUGGING INTERVALS		
10 FROM TO 0 2	TOPSOIL LO	)G	FROM	IU LI	THO. LOG (cont.) or	I LUGUING INTERVALS		
	CLAY							
18 36	FINE SAND							
	MEDIUM FINE SAND							
54 60	SHALE							
			Notes:					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
Kansas Water Well Contractor's License No. 911								
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.  KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.								
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66012 1567. Telephote KSA 82a-1212  Visit us at http://www.kdheks.gov/waterwell/index.html								