WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 Sedgwick NE 1/4 1/4 31 Т 26 S R 1W E/W Distance and direction from nearest town or city street address of well if located within city? 2324 N. Park Ridge Wichita, Kansas **SHARP HOMES** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2131 N. Collective Ste. #A Wichita, Kansas CITY, STATE: Application Number: ZIP CODE <u>70</u> LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: **ELEVATION:** WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: WELL'S STATIC WATER LEVEL 10/14/16 Well water was Pump test data: ft. after hours of pumping @ NW NE apm Est. Yield: Well water was ft. after hours of pumping @ gpm Ī Bore Hole Diameter 12 ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE 3. Feedlot S₩ 1. Domestic 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning (NO) ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 50 Blank casing diameter Dia. Dia. in. to ft., in to ft. 12 Casing height above land surface: in.. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 7. Torch cut 9. Drilled holes 1. Continuous slot 5. Gauzed wrapped 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) 50 70 SCREEN - PERFORATION INTERVAL From to ft., From to ft. ft. From to ft.. From to ft. 24 **GRAVEL PACK INTERVALS:** ft. 70 From to ft., From to ft. ft. From ft . From ft. ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From 4 ft. 24 ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 12 ft plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From Τо 0 topsoil 18 clay 18 45 fine sand 45 70 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. under my jurisdiction and

10/14/16 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/17/16 under the business name of Harp Well and Pump Service by (signature)

Todd S. Harp