WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE NWSW31 26 R 1W E/W 1/4 Т S 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 3203 N. Chambers Wichita, Kansas **SHARP HOMES** WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 2131 N. Collective Ste. #A Wichita, Kansas CITY, STATE ZIP CODE: Application Number: 4 DEPTH OF COMPLETED WELL: 70 fŧ ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX Depth of groundwater Encountered: ft. ft ft. N WELL'S STATIC WATER LEVEL 26 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/17/17 Pump test data: Well water was ft. after hours of pumping @ gpm NW ΝE Est. Yield: Well water was ft. after hours of pumping @ apm apm Φ ₩ 12 to 70 and Bore Hole Diameter ft WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE 1 Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) S Was Water Well Disinfected? (YES 5 TYPE OF CASING USED CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 50 Dia. ft.. Dia ft. Blank casing diameter to ft., in to in to 12 2.35 Casing height above land surface Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1. Steel 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 9. Drilled holes 11. None ( open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 6. Wire wrapped 8. Saw cut 10. Other (specify) 2 Louvered shutter 4. Key punched SCREEN - PERFORATION INTERVAL 50 ft... From From to ft to ft. From ft. to ft.. From ft to ft. 24 ft to 70 GRAVEL PACK INTERVALS: ft., From ft. From to ft ft. From to ft... From ft. Other 6 **GROUT MATERIALS** 2. Cement Grout 3. Bentonite bentonite hole plug 1. Neat cement 4 ft. 24 ft Grout Intervals From From ft. From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 10 ft. plus South Direction from well? LITHOLOGIC LOG From Τo LITHOLOGIC LOG From Τo 0 3 topsoil 3 18 clay fine sand 18 45 medium sand 45 **70** 

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 2/17/17 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/20/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp