Form WWC-5 WATER WELL RECORD KSA 82a-1212 TOWNSHIP NUMBER SECTION NUMBER LOCATION OF WATER WELL: FRACTION RANGE NUMBER Sedgwick NE NE SE 1/4 32 26 S 1WDistance and direction from nearest town or city street address of well if located within city? 4406 Cimarron Wichita, Kansas MCCLELLAN ENTERPRISES, INC. WATER WELL OWNER Board of Agriculture, Division of Water Resource 1108 W. 34th N. RR#,ST. ADDRESS,BOX # ZIP CODE: 67204 Wichita, Kansas Application Number: CITY, STATE: 40 ELEVATION: LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft 10 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 2/22/17 Pump test data Well water was ft. after hours of pumping @ apm NW NE ft. after Est. Yield: gpm Well water was hours of pumping @ gpm <u>o</u> Ē₩ Bore Hole Diameter 12 to 40 and WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE 1. Domestic SW 3. Feedlot 12. Other (Specify below) 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES S (YES) Was Water Well Disinfected? submitted 5 TYPE OF CASING USED CASING JOINTS: Glued 9. Other (Specif / below) Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 30 Dia ft. Blank casing diameter to 12 2.35 Weight: lbs. / ft. Wall thickness or gauge No. Casing height above land surface: .214 TYPE OF SCREEN OR PERFORATION MATERIAL 7. PVC 11. Other (specify) 9 ARS 1. Steel 3. Stainless Steel 5. Fiberglass 12. None used (open hole) 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 7. Torch cut 1. Continuous slot 10. Other (specify) 2. Louvered shutter 4. Key punched Wire wrapped 8. Saw cut 30 40 SCREEN - PERFORATION INTERVAL ft., From to ft ft to ft From to ft., From ft. to ft. 24 ft. GRAVEL PACK INTERVALS to 40 From ft., From ft. to ft. From ft. to ft., From ft. to ft. GROUT MATERIALS: Other 6 bentonite hole plug 1. Neat cement 2. Cement Grout Bentonite Grout Intervals: From 24 ft., ft. to ft.. From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit North How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG From Τo LITHOLOGIC LOG From Τо 3 topsoil 3 8 clay 8 15 fine sand 15 40 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or under my jurisdiction and

2/22/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)