			WATER W	ELL RE	CORD	Form W\	VC-5 K	SA 82a-12	12			
1 LOCATION OF WATER WELL:			FRACTION	C.F.			TION NUMBER		IIP NUMBER	RANGE NU		
Sedgy			SE 1/4		1/4 SW	1/4	21	<u> </u>	26 S	R 1V	/ E/W	
1	N. Sheffa	n nearest town or city s	ichita, Kans		AUTIN CITY?							
2 WATER WELL OWNER: GREY CONSTRUCTION												
RR#,ST. ADDRESS,BOX #: P.O. Box 12107												
	CITY,	STATE: Wich	ita, Kansas			Z	IP CODE:		Application Nun	nber:		
	E WELL'S LO		EPTH OF COM	PLETED W	/ELL:	68 ft.		ELEVATION:				
WITHA	N "X" IN SEC		th of groundwat	er Encounte	ered:	f	t.		ft.		ft.	
		WE	JRFACE MEAS	SURED ON mo/o	day/yr: 6/12	4/17						
	-MM	- NE		Pump test data: Well water was				ft. after hours of pumping @ gpm				
Mile w			Est. Yield:	gpm er 12		vater was to	68 ft	ft, after . and		s of pumping @	gpm ft.	
₹ w		' '	ore Hole Diamete ELL WATER TO			10	uo ii	, and	in.	to 11 Inje	ction well	
WELL WATER TO BE USED AS: 9. Dewatering 11. Injection of the state of												
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well												
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO												
5 TYPE OF CASING LISED: CASING COUNTS: Cluid Threaded												
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded Clamped												
	2. PVC	> 4. ABS	6. Asbest	os-Cement	8. Concrete	e tile SL	/K-20				·	
Blank cas	ing diamete	r 5 i	in. to	48 ft.	, Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214												
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7, PVC 9, ABS 11. Other (specify)												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Otner (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)												
2. Louve	2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)											
		TION INTERVAL	From	48	ft.	to 68	ft.,	From	4	40	4	
SCREEN -	- FERI ORA	IION INTERVAL	From	70	ft.	to oc	ft.,	From	ft. ft.	to to	ft. ft.	
G	RAVEL PA	CK INTERVALS:	From	24	ft.	to 68	ft.,	From	ft.	to	ft.	
			From		ft.	to	ft.,	From	ft.	to	ft.	
6 GROU	JT MATERI	ALS: 1 Noat 6		2 Con	nent Grout		3. Bentonite			tonite hole pl		
GROUT MATERIALS: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From							. to	ft.,	From	ft. to	—s ft.	
What is the nearest source of possible contamination:							10. Livestock pens		cticide storage	15. Oil well/0	Sae well	
1. Septic tank 4. Lateral lines							Fuel storage 14. Abandon wa			46 Other (anesity helesy)		
2. Sewe		5. Cess P	GOI	_	_		_	IM. ADAII	Idoli Walei Well	, ,	• •	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? South How many feet?									many feet? 10	ft. plus		
From	То		LITHOLOG	IC LOG		From	То			OGÍC LOG		
0	3	topsoil					1	ļ				
3	22	clay and sand	mix				<u> </u>					
<u>22</u> 40	68	fine sand medium sand				<u> </u>						
<u> </u>							-					
	 	<u> </u>				+	+					
								ļ			·	
	<u> </u>	<u></u>					+					
<u> </u>	<u> </u>	<u> </u>										
7 Cont	tractor's or I	_andowner's Certific			1. Construc	ted 2. r	econstructe	d or 3.	plugged	under my jurisdic	tion and	
was completed on (mo/day/year) 6/12/17 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/16/17												
under th	ne business	name of Harp	Well and Pu	ımp Serv	vice	by (:	signature)	7	Add.	Harr	•	