WATER WELL RECORD F	orm WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NU		RANGE NUMBER
Sedgwick SW 1/4 SW 1/4 SE	1/4 13	T 26 S	R IW E/W
Distance and direction from nearest town or city street address of well if located within city?			
East of Sheridan, North of 53rd St. N. Wichita, I WHICHITA, CITY OF	Kansas		
RR#,ST. ADDRESS,BOX #: 455 N. Main		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE	E: Application Nu	mber: 20170098
3 LOCATE WELL'S LOCATION 4 DEPTH OF CAMPAGE VELL: 38		ELEVATION:	
WITH AN "X" IN SECTION BOX:	 ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 13		D SURFACE MEASURED ON mo/	
Pump test data: Well wat			s of pumping @ gpm
1 1 "" 1 " 1 1			s of pumping @ gpm
Est. Yield: gpm Well wat	to	ft. and in.	to ft.
WELL WATER WAS USED AS:		9. Dewater	ing 11. Injection well
1. Domestic 3. Feedlot 5. Public wa		wn and garden only conditioning 10. Monitori	12, Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w Was a chemical/bactedological sample submitted to 0		. 16	what mo/day/yr was sample
submitted		as Water Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought fron 7. Fiberglass	9. Other (Spo	ecity below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	SDD 36		Welded Clamped
2. FVC 4. AB3		<i>a</i> .	
Blank casing diameter 8 in. to ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height Casand surface: 36 in., Weight:	lbs. / ft.	Wall thickness or gau	ge No.
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos		
SCREEN OR PERFORATION OPENINGS ARE:	V-77 15555155		,
Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify) N	
		• • • •	II PA
SCREEN - PERFORATION INTERVAL From ft. to		From ft.	to ft.
From ft. to	****	From ft,	to ft.
GRAVEL PACK INTERVALS: From ft. to	14.4	From ft.	to ft.
From ft. to) ft.,	From ft.	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bento	onite Other bent	tonite hole plug
Grout Intervals: From 3 ft. to 24 ft., From What is the nearest source of possible contamination:	ft.	to ft., From	ft, to ft,
1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
_ ·	l1. Fuel storage	14. Abandon water well	16. Other (specify below)
	12. Fertilizer storag	e	
Direction from well? North		How many feet? 10	ft. plus
From To LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
	0 3	compacted clay	
· · · · · · · · · · · · · · · · · · ·	3 24 24 38	1 5	
	 	chlorinated gravel	-
	<u> </u>		
		 _	
	1.		
	 		
	 		
	 		
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2 *05000	mod or 3 plumond	under my juriedictics and
E14.014E			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/19/17			
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourb			