WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE SE SW31 26 R 1W s 1/4 1/4 1/4 Т E/W Distance and direction from nearest town or city street address of well if located within city? 3036 N. Cortina Wichita, Kansas **BROWN**, Michael WATER WELL OWNER: Board of Agriculture, Division of Water Resource 3036 N. Cortina RR#,ST. ADDRESS,BOX #: ZIP CODE: 67205 Wichita, Kansas CITY, STATE Application Number: 4 DEPTH OF COMPLETED WELL: 68 **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/21/17 Pump test data: Well water was ft. after hours of pumping @ NW NEapm Est. Yield: Well water was hours of pumping @ ft. after apm gpm 12 Ξ to 68 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (YES) Was Water Well Disinfected? 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS 48 Blank casing diameter ft., Dia ft.. Dia ft. to 12 Weight: Casing height above land surface: in., 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4 Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 8. Saw cut 10. Other (specify) 2. Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 48 68 fŧ From to ft. From ft. ft. to ft. From to ft.. From ft. to ft. 24 GRAVEL PACK INTERVALS: ft. to 68 ft., From From ft to ft. From ft. to ft., From ft. to ft. 6 **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 4 ft. 24 ft., From ft. to ft., From ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4 Lateral lines 16. Other (specify below) 11. Fuel storage 5. Cess Pool 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 12. Fertilizer storage 9. Feed yard Watertight sewer line 6. Seepage pit How many feet? 10 ft. plus South Direction from well? LITHOLOGIC LOG From To LITHOLOGIC LOG From То 0 3 topsoil 3 20 clav 20 35 fine sand 35 medium sand 68 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3. plugged under my jurisdiction and

was completed on (mo/day/year) 8/21/17 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/22/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp