		WATER W	ELL RECORD) Form	n WWC	C-5 KS	SA 82a-121	2		
1 LOCATION OF WATE	ER WELL:	FRACTION SE 1/4	SW 1/4	SW 1/4		N NUMBER			RANGE N	
Sedgwick Distance and direction from	om nearest town or city			SW 1/4	1	21	T 20	5 S	K IV	W E/W
3875 N. Estancia Ct. Wichita, Kansas										
2 WATER WELL OWNER: MC CLELLAN ENTERPRISES INC. Board of Agriculture, Division of Water Resource										
RR#,ST. ADDRESS		W. 34th N. iita, Kansas			7ID (CODE: 67	7204	Application Nun		Tale: Nessarde
3 LOCATE WELL'S LO		DEPTH OF COMP	PLETED WELL:	103	ft.	CODE: V	ELEVATION:	Аррисацоп нип	iber.	
WITH AN "X" IN SE	CTION BOX:	oth of groundwater			ft.			ft.		ft.
		ELL'S STATIC WA	_	2 FT.	BELOW	LAND SU	RFACE MEASU	IRED ON mo/o	day/yr: 8/2	1/17
	NE			/ell water wa			ft. after		of pumping @	gpm
w Mile		Est. Yield: ore Hole Diameter	0,	Vell water wa	as to 10 .	3 ft.	ft, after and	hours in.	of pumping @ to	gpm ft.
- "		ELL WATER TO B	BE USED AS:					0 Dewateri	44 1.1	ection well
SW SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below										
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning Was a chemical/bacteriological sample submitted to Department? YES NO 10. Monitoring well 10. Monitoring well 10. Honorogy was sample 11. If yes, what mo/day/yr was sample 11.										
submitted Was Water Well Disinfected? YES NO										
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded										
1. Steel 3. RPM (SR) Welded Clamped 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26										
Blank casing diamet		in. to	86 ft., D	ia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)										
2. Louvered shutt	er 4. Key pu	unched 6. V	Wire wrapped	<	8. Saw	cut	10. Oth	er (specify)		
SCREEN - PERFOR	ATION INTERVAL	From	86 ft.	to	103 f	ft.,	From	ft.	to	ft.
		From	ft.	to	f	ft.,	From	ft,	to	ft.
GRAVEL PA	ACK INTERVALS:	From	24 ft.	to	103 f	t.,	From	ft.	to	ft.
		From	ft.	to	f	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout					3. 6	Bentonite	e Other bentonite hole plug			
Grout Intervals:	From 4	ft. to	24 ft., F	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens						13. Insecti	cide storage	15. Oil well/	Gas well	
2. Sewer lines	5. Cess P	, 9	. Sewage lagoon	11. Ft	uel storaç	ge	14. Aband	on water well	16. Other (s	pecify below)
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
From To	East	LITHOLOGIC	CLOG	TF	rom	То	How ma	INTHOLO	GIC LOG	
0 3	topsoil	LITTIOLOGIC	0 200		10111			LITTIOLC	OIO LOO	
3 8	clay									
8 20 20 75	fine sand medium sand									
75 86	clay									
86 101	medium sand									
101 103	gray shale									
7 Contractor's or	Landowner's Certific	cation: This water	well was 1 Const	tructed	2 reco	nstructed	or 3.	plugged	under my jurisdic	tion and
was completed on (mo/day/year) 8/21/17 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/22/17										
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										