## WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SW NWNE 27 26 R 1W Sedgwick Τ S E/W 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 6218 W. Kollimeyer Wichita, Kansas **ROBL CONSTRUCTION** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 5842 W. 21st N. RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE ZIP CODE Application Number: 40 ELEVATION: 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 7/28/17 ft. Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: \_ γ<del>i∈</del>-Pump test data: Well water was ft. after hours of pumping @ apm NW Est. Yield: Well water was ft. after hours of pumping @ gpm apm Ē₩ 12 to 40 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1 Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) S Was Water Well Disinfected? (YES 5 TYPE OF CASING USED CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS **30** 5 Blank casing diameter to ft.. Dia. in. ff Dia in. ft. to to 12 2.35 Wall thickness or gauge No. in... Weight: lbs. / ft. Casing height above land surface: .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) 2 Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 30 ft. ft., to From From ft. to ft. ft. to ft., From From ft. ft. to 24 GRAVEL PACK INTERVALS: to 40 From ft.. From ft. to ft. ft From to ft.. From to ft. Other **GROUT MATERIALS:** bentonite hole plug 2. Cement Grout 3 Bentonite 1. Neat cement 4 24 Grout Intervals: From ft. ft.. From ft. to ft., From What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool None Yet 12. Fertilizer storage 9. Feed yard 3. Watertight sewer line 6. Seepage pit How many feet? Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From To From To 0 tonsoil 3 8 clav fine sand 8 18 medium sand 18 40

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and

was completed on (mo/day/year) 7/28/17 Kansas Water Well Contractor's License No. 236

and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb