		WATER W	ELL RECORE	D For	m WW	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATE	R WELL:	FRACTION			SECT	ION NUMBER		P NUMBER	RANGE N	UMBER
Sedgwick		SE 1/4	SE 1/4	SW 1	/4	27	Т 2	6 S	R 1W	V E/W
Distance and direction from nearest town or city street address of well if located within city?										
3875 N. Estancia Ct. Wichita, Kansas										
2 WATER WELL OWNER: MCCLELLAN ENTERPRISES, INC.										
RR#,ST. ADDRESS,BOX #: 1108 W. 34th N. Board of Agriculture, Division of Water Resource										
CITY,	STATE: Wicl	hita, Kansas			ZI	P CODE: 6	7204	Application Num	nber:	
3 LOCATE WELL'S LO	CATION 4	DEPTH OF COMP	LETED WELL:	75	ft.		ELEVATION:			
WITH AN "X" IN SEC	CTION BOX:	ath of aroundwater	Encountered		ft.			ft.		ft.
N N		epth of groundwater		12 F					0/16	
	, w	ELL'S STATIC WA				W LAND SU	JRFACE MEAS			9/17
NW	NE		•	Vell water			ft. after		of pumping @	gpm
M M		Est. Yield:		Vell water		-	ft. after		of pumping @	gpm
1 1 1	· ·	Bore Hole Diameter			to 7	5 ft.	and	in.	to	ft.
WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 2. Lawn and garden only 12. Other (Specify below)										
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted was Water Well Disinfected? (YES) NO										
5 TYPE OF CAS									Glued	
1. Steel	3. RPM (SI	R) 5. Wrought	Iron 7. Fibe	erglass		her (Specify	Delow) CA	SING JOINTS: (Welded	Threaded
2. PVC	> 4. ABS	6. Asbestos	s-Cement 8. Cor	ncrete tile	SDF	R-26			weided	Clamped
Blank casing diameter		in. to	55 ft., D)ia.	in.	to	ft.,	Dia.	in. to	ft.
	-	10	,							п.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4	. Galvanized	6. Concrete T	ile 8. RMP	' (SR)	10. As	sbestos-Cer	nent 12. No	one used (open	hole)	
SCREEN OR PERFO	RATION OPENING	GS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open ho									pen hole)	
2. Louvered shutte	r 4. Keyp	upched 6 V	Wire wrapped		8. Sa	w cut	10 Oth	er (specify)		
2. Louvered shallo	ч ч. Кеур						10. 011	er (apeeny)		
SCREEN - PERFORA	TION INTERVAL	From	55 ft.	to	75	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVALS:	From	24 ft.	to	75	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	4-	
	41.0						11011		to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug										
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.										
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well									as well	
1. Septic tank 4- Lateral miles										
2. Sewer lines 5. Cess Pool										
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage										
Direction from well?	East				-		How m	any feet? 10 1	_	
From To		LITHOLOGIC	LOG		From	To		LITHOLC	GIC LOG	
	topsoil									
3 8	clay									
8 18	fine sand	3								
<u>18 68</u> 68 75	medium sand	1								
	clay									
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and										
was completed on (mo/day/year) 9/15/17 and this record is true to the best of my knowledge and belief.										
Kansas Water Well	Contractor's Licen	ise No. 236	This w	ater well r	ecord was	s completed		,	9/17	
Kansas Water Well under the business				vater well re		s completed gnature)		,	9/17 . Harp	