WATER WELL RECORD	Form WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick SW 1/4 SE 1/4 NE	1/4 33 T 26 S R 1W E/W
Distance and direction from nearest town or city street address of well if located within city?	
Lot across from 3442 N. Beach Club Wichita, Kans	as
2 WATER WELL OWNER: PIER 37	
RR#,ST. ADDRESS,BOX #: 3450 N. Beach Club	Board of Agriculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: Application Number:
	0 ft. ELEVATION:
WITH AN "X" IN SECTION BOX:	
Depth of groundwater Encountered:	ft. ft. ft.
WELL'S STATIC WATER LEVEL 12	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/2/17
Pump test data: Well w	ter was ft. after hours of pumping @ gpm
👲 🛛 🧹 Est. Yield: gpm Well w	ater was ft. after hours of pumping @ gpm
E Est. Yield: gpm Well w Bore Hole Diameter in.	to ft. and in. to ft.
WELL WATER	9. Dewatering 11. Injection well
1. Domestic 3. Feedlot 5. Public w	ater supply . Lawn and garden only 12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field	vater supply 8. Air conditioning 10. Monitoring well
S Was a chemical/bacteriological sample submitted to	
submitted	Was Water Well Disinfected? YES NO
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglas:	9. Other (Specify below) CASING JOINTS: Glued Threaded
1. Steel 3. RPM (SR)	Weided Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete	tile
Blank casing diameter 5 in. to ft., Dia.	in. to ft., Dia. in. to ft.
Casing height and surface: 36 in., Weight:	lbs. / ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	
	9. ABS 11. Other (specify) N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify) N/A
SCREEN - PERFORATION INTERVAL From ft. t	D ft., From ft. to ft.
From ft. t	D ft., From ft. to ft.
GRAVEL PACK INTERVALS: From ft.	o ft., From ft. to ft.
From ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite Other bentonite hole plug
Grout Intervals: From ft. to ft., From	ft. to ft., From 3 ft. to 23 ft.
What is the nearest source of possible contamination:	10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
1. Septic tank 4. Lateral lines	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel storage 14. Abandon water well 16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage
Direction from well?	How many feet?
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
	0 3 compacted topsoil
	3 23 bentonite hole plug
	23 50 chlorinated gravel
7 Contractor's or Landowner's Certification: This water well was 1. constructe	d 2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 10/2/17 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/4/17	
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harb