WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER FRACTION R 1W E/W NE NW27 26 SE Т Sedgwick 1/4 1/4 1/4 S Distance and direction from nearest town or city street address of well if located within city? 4315 N. Ridge Port Wichita, Kansas **BLUE CUSTOM HOMES LLC** WATER WELL OWNER: Board of Agriculture, Division of Water Resource 106 S. Breezy Pointe Circle RR#,ST. ADDRESS,BOX #: ZIP CODE: 67235 Wichita, Kansas CITY, STATE 35 4 DEPTH OF COMPLETED WELL: **ELEVATION** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 11 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/15/18 Pump test data: Well water was ft. after hours of pumping @ ΝE gpm NW Est. Yield: Well water was ft. after hours of pumping @ gpm qpm ⋝ ٧ Bore Hole Diameter 12 to 35 and ft. WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SE SW 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC 5 25 Dia. Dia. Blank casing diameter ft. to 12 2.35 Casing height above land surface: in Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) 25 35 SCREEN - PERFORATION INTERVAL to ft., From ft. to ft. From to ft., From to ft. 24 GRAVEL PACK INTERVALS: ft. to 35 From ft., From ft. ft. From From ft. ft. GROUT MATERIALS Other bentonite hole plug 2. Cement Grout 3. Bentonite Grout Intervals: From ft. ft. From ft From to ft.. ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3 Watertight sewer line North How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From To From Τо 3 topsoil 3 7 clay 7 15 fine sand 15 35 medium sand

Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and was completed on (mo/day/year) 3/15/2018 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/16/18

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp