WATER WELL RECORD	D Form WV	NC-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION	SEC	TION NUMBER	TOWNSHI	PNUMBER	RANGE N	NUMBER
Sedgwick SW 1/4 SE 1/4	SE 1/4	29	T 26 S R 1W E/W			
Distance and direction from nearest town or city street address of well if located within city? 9010 W. 37th N. Wichita, Kans	sas					
2 WATER WELL OWNER: CYPRESS POINT LLC	-				***	
RR#,ST. ADDRESS,BOX #: 9010 W. 37th				Board of Agric	culture, Division of	Water Resource
CITY, STATE: Wichita, Kansas	z	IP CODE: 6	7213	Application Num	ber:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF PUMPEDED WELL:	50 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered:	ft	t.		ft.		ft.
	16 FT. BELO	OW LAND SU	JRFACE MEASI	JRED ON mo/d	ay/yr: 5/5	5/18
Pump test data: V	Vell water was		ft. after		of pumping @	gpm
Est. Yield: gpm V Bore Hole Diameter in.	Well water was		ft. after	hours	of pumping @	gpm
	to	ft.	and	in.	to	ft.
WELL WATER BE USED AS:		712		9. Dewaterii	ng 11. Inje	ection well
	blic water supply			レ 10. Monitorin		specify below
2. Irrigation 4. Industrial 6. Oil Was a chemical/bacteriological sample subm	field water supply	y 8. Aircor YES	NO NO		vhat mo/day/yr	was sample
submitted	- Department:		Vater Well Disin		YES	NO
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fibe	erglass 9. C	ther (Specify	below) CAS	SING JOINTS:	Glued	Threaded
	ncrete tile				Welded	Clamped
	Dia. in.	to	ft.,	Dia. i	n. to	ft.
Casing height babbe land surface: 4 in., Weight		lbs. / ft.				11.
TYPE OF SCREEN OR PERFORATION MATERIAL:	grit.	105. / 11.	waii ii	ickness or gaug	e No.	
Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. A	ABS	11. Ot	her (specify) N	J/A	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMF	P (SR) 10. A	Asbestos-Cer	ment 12. No	one used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. T c	orch cut	9. Dril	led holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. S a	aw cut	10. Oth	er (specify) N/	'A	
COREEN REPERDATION WITHOUT					••	
11011	to	ft.,	From	ft,	to	ft.
From ft. GRAVEL PACK INTERVALS: From ft.	to	ft.,	From	ft.	to	ft.
11011	to	ft.,	From	ft.	to	ft.
From ft.	to	ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug						lug
Grout Intervals: From 4 ft. to 27 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:						
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestoo	ck pens	13. Insect	icide storage	15. Oil well/	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify be						pecify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well?			How ma	any feet?		
From To LITHOLOGIC LOG	From	То		LITHOLO	GIC LOG	
	0	4	compacted			
	4		bentonite h			
	27	50	chlorinated	gravel		
					- 10	
						
		 				
				·		
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and						
was completed on (mo/day/year) 5/5/18 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/8/18						
under the business name of Harp Well and Pump Service by (signature)						
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp						