			WATERV	VELL RE	CORD	Form V	V V V C-5	KSA 82a-12	12			
1 1	ON OF WATE	R WELL:	FRACTION	N/NY/			ECTION NUMB	1	P NUMBER	RANGE N		
Sedg			SW 1/4		1/4 SW	1/4		T2	6 S	R 11	V E/W	
	d direction from E. Planta	m nearest town or city s			thin city?							
	ER WELL O		TSON, Cod	Kansas								
	ADDRESS		E. Plantation						Board of Agr	culture, Division of \	Water Resource	
			e, Kansas				ZIP CODE:	67101	Application Nun	nber:		
3 LOCAT	E WELL'S LO	OCATION 4	DEPTH OF COM	PLETED WE	ELL:	48	ft.	ELEVATION:				
<mark> With </mark>	AN "X" IN SEC N	CTION BOX:	oth of groundwate				ft.		ft.		ft.	
			ELL'S STATIC W			FT BE		SURFACE MEAS		tay/yr: 6/11	2/18	
	NW	NE		ump test dat		ater was		ft. after		of pumping @	gpm	
<u>a</u>			Est. Yield:	gpm	Wellw	vater was		ft. after		of pumping @	gpm	
W Wile		E Bo	ore Hole Diamete	er 12	in.	to	48	ft. and	in.	to	ft.	
$ - \times$	sw		ELL WATER TO				7 1 200	and garden on	9. Dewateri	ng 11. Inje	ction well	
		1 1 "		B. Feedlot					10. Monitorii		pecify below	
	S		as a chemical/bact		6. Oil field		. ,	NO		what mo/day/yr	was sample	
			omitted		- Pio Saoriiiii (Co			Water Well Disir	fected?	YES	NO	
		SING USED:	5. Wrough	nt Iron	7. Fiberglas	is 9	Other (Spec	ify below) CA	SING JOINTS: (Glued	Threaded	
	1. Steel	3. RPM (SR	()			C	DR-26			Welded	Clamped	
	2. PVC	> 4. ABS		os-Cement	8. Concrete	: tile						
	sing diamete	_	in. to	28 ft.,	Dia.	in	to	ft.,	Dia.	in. to	ft	
_	-	e land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall t	nickness or gaug	ge No214		
1. Stee		OR PERFORATION 3. Stainless Steel	MATERIAL: 5. Fiberglas:		7. PVC		. ABS	11 0	ther (specify)			
2. Bras		I. Galvanized	6. Concrete		8. RMP (SR		. Asbestos-C		one used (open	hole)		
		PRATION OPENING		1110	o. row (ore	, ,	, Asbestos-C	ement 12.14	one asea (open	noie)		
	inuous slot			Gauzed wr	anned	7	Torch cut	9 Dri	lad halos	11 None /	onen hole)	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped									9. Drilled holes 11. None (open hole) 10. Other (specify)			
			inched 0.				Saw cut	10. Otr	ier (specity)			
SCREEN	- PERFORA	TION INTERVAL	From			to 48	ft.,	From	ft.	to	ft.	
			From			to	ft.,	From	ft.	to	ft	
G	RAVEL PA	CK INTERVALS:	From	24	ft.	to 48	ft.,	From	ft.	to	ft.	
			From		ft.	to	ft.,	From	ft.	to	ft.	
	UT MATERI	· · · · · · ·			ent Grout		3. Bentoni	te	Other bent	onite hole pl	ug	
									ft. to	ft.		
What is the nearest source of possible contamination: 1 Septic tank 4. Lateral lines 7. Pit privy 1						10. Lives	ock pens	13. Insec t	icide storage	15. Oil well/0	Gas well	
						11. Fuel	storage	14. Aband	14. Abandon water well 16. Other (specify below)			
3. Water	rtight sewe	er line 6. Seepag	ge pit	9. Feed yard	d	12. Fertil	zer storage					
Direction	from well?	East						How m	any feet? 20 f	ft. plus		
From	То	L	LITHOLOGI	C LOG		Fror	п То		LITHOLC	GIC LOG		
0	3	topsoil										
6	25	clay fine sand										
25	48	medium sand						+				
		-										
						-						
											**	
	-											
-1												
Cont	tractor's or L	_andowner's Certific		r well was 1	constructe	ed) 2.	reconstruct	ed or 3.	plugged	under my jurisdic	tion and	
was cor	mpleted on	(mo/day/year)	6/12/18	;	and this recor	d is true to	the best of m	y knowledge and	belief.			
Kansas	Water Well	Contractor's Licens	se No. 236		This water	well record	was complete	ed on (mo/day/ye	er) 6/1	4/18		
under th	ne business	name of Harn V	Well and Pu	mp Servi	ce	bv	(signature)	$\boldsymbol{\tau}$	2.55	Haim		
		under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										