		WATER \	WELL RE	ECORD	Form W	NC-5 k	KSA 82a-1	1212			
						CTION NUMBE	R TOWN				
Sedgwick	from populations or	SE 1/		1/4 NI	E 1/4	34	Т	26 S	R	1W	E/W
3625 N. Ho		Vichita, Kansa		vitnin city?							
2 WATER WELL OWNER: MULLIN CONSTRUCTION LLC											
RR#,ST. ADDRE		O. Box 529						Board of	Agriculture, Division	on of Wat	er Resource
CIT	TY, STATE: \mathbf{G}	oddard,Kansa	s			IP CODE: 6	67052	Application	Number:		
3 LOCATE WELL'S	S LOCATION	4 DEPTH OF COM	MPLETED W	/ELL:	48 ft.		ELEVATIO	N:	•		
WITTAN X IN	N SECTION BOX:	Depth of groundwa	ter Encounte	ered:	1	t.		ft.			ft.
		WELL'S STATIC V	VATER LEV	EL 12	FT. BEL	OW LAND S	URFACE ME	ASURED ON n	no/day/yr:	6/4/1	8
NW	NE ^	ı	Pump test da		water was		ft. after		ours of pumping		gpm
W Wile	F	Est. Yield: Bore Hole Diame	gpm ter 12		water was to	48 #	ft. after t. and	in	ours of pumping	to	gpm ft.
-		WELL WATER TO			10	10 11	t. and		4.4		
sw	SE WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 12. Other (Specify below) 12. Other (Specify below)										
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well											
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted was Water Well Disinfected? YES NO											
5 TYPE OF C	CASING USED:	5. Wroug	ht Iron	7. Fibergla	ss 9. (Other (Specif	fy below) (CASING JOINT	S: Glued	Т	hreaded
1. Steel	3. RPM	I (SR)		8. Concrete	ST.	R-26	,		Welded		Clamped
2. PVC Blank casing dian	4. ABS		tos-Cement 38 ft.		e lile						
		13	38 ft.,		in.	to	ft.,	Dia.	in. to		ft.
	ove land surface: :N OR PERFORAT	,		Weight:	2.35	lbs. / ft.	Wa	Il thickness or g	gauge No.	.214	
1. Steel	3. Stainless Stee		ss <	7. PVC	9	ABS	11.	Other (specify)		
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PER	RFORATION OPEN	NINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											en hole)
2. Louvered shi	utter 4. Ke	y punched 6	6. Wire wrap	ped	8. S	aw cut	10. 0	Other (specify)			
SCREEN - PERFO	RATION INTERVA	AL From	38	ft.	to 48	ft.,	From	ft.	to	1	ft.
		From		ft.	to	ft.,	From	ft.	to		ft.
GRAVEL	PACK INTERVALS	S: From	24	ft.	to 48	ft.,	From	ft.	to)	ft.
		From		ft.	to	ft.,	From	ft.	to)	ft.
6 GROUT MAT	ERIALS: 1. No	eat cement	2. Cem	nent Grout		3. Bentonite	e	Other b e	entonite hol	e plug	ŗ.
Grout Intervals		4 ft. to	o 24	ft., From	n ft	. to	ft.,	From	ft.	to	ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 15 Oil well/Gas								s well			
2. Sewer lines	5. Ce s	ss Pool	8. Sewage	lagoon	11. Fuel st	orage	14. Ab a	andon water w	ell 16. Othe	r (spec	cify below)
3. Watertight se		epage pit	9. Feed yar	rd	12. Fertilize	er storage					
Direction from we			10100				How	many feet? 1			
From To		LITHOLOG	IC LOG		From	То		LITHO	LOGIC LO	3	<u></u>
3 8	topsoil clay					-					
8 20	fine sand										
20 47 47 48	medium sa	ınd				ļ					
47 48	clay				-						
						<u> </u>					
											
									_		
					_	_					
7 Contractor's	or Landowner's Ce	ertification: This water	er well was 1	1. construct	ted 2 r	econstructe	d or 3.	plugged	under my jur	isdiction	n and
	on (mo/day/year)	6/4/18					knowledge a		, ,		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/6/18											
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp											
ander the busine		ip wen and Pt	mp serv	ice		ignature)		i oaa	s. Ha	rp	